







Exterior Concrete Repair & Restoration System™

The Complete System for Restoring and Repairing Exterior Concrete Surfaces!



Don't replace the slab....restore it with ARDEX and save time, money and hassle!



ARDEX Exterior Concrete Repair & Restoration System™



When driveways, sidewalks, loading docks, curbs, plazas, pool decks or any exterior concrete surface is in need of repair, ARDEX provides a comprehensive system of technologically advanced products to make damaged or spalled concrete look like new.

ARDEX fast-track, high-performance exterior products save significant time and cost in the restoration and repair of concrete surfaces. Whether it's a finished concrete look or a customized surface design using color or stencils, ARDEX has the right product for the job!

ARDEX K 301™

Exterior Self-Leveling Concrete Topping

The only high-performance exterior self-leveling product on the market that provides a fast-track new finish for damaged concrete surfaces. Can also be used as an indoor underlayment or topping for new building construction or existing building renovations that are not yet closed-in and will be exposed to weather and other external elements.



BEFORE

AFTER

- Walk on 2 to 3 hours
- Apply sealer in as little as 24 hours
- Freeze-thaw resistant Wear surface or underlayment Makes badly spalled concrete look like new!

ARDEX CD™

Concrete Dressing

Resurfaces concrete to a "new-finish". ARDEX CD creates a new wear surface that can be broom finished for a slip resistant texture. It can also be stenciled or colored for unlimited custom design options.

- Easy to apply & hardens fast
- Freeze-thaw resistant
- Walk on in 2 to 3 hours
- Drive on in 8 hours
- Available in regular and fine formulas



ARDEX CPTM Concrete Patch



Repair, re-slope or reform any concrete surface with this fast-track Portland cement-based patch. Use ARDEX CP to fill spalls, gouges, dormant cracks, "birdbaths" and other low areas in concrete surfaces.

- Easy to apply
- Hardens fast
- Freeze-thaw resistant
- Trowelable for patching, filling or sloping
- Use to reform steps or curbs

ARDEX CGTM Concrete Guard

A high-performance, high-solids acrylic sealer for uncoated concrete toppings. ARDEX CG is a very durable sealer that reduces water penetration into the concrete. Available in Clear, Gray and White/Tintable Base. The White/Tintable Base can be colored to match virtually any color. The tinting can be done through your local paint supplier using standard pigments for waterborne acrylic sealers, such as Sherwin-Williams' Blend-A-Color or similar.

- Easy to apply & quick drying
- Durable & abrasion resistant
- Non-flammable/UV stable
- For exterior or interior use



For more information about

these and other ARDEX

products, including

Underlayments & Toppings,

please visi

www.ardex.com

www.systemonesolutions.con

ARDEX Exterior Wall Patching & Finishing System™ The Complete System for Patching & Repairing Concrete and Maconing Wallet

Concrete and Masonry Walls!

This powerful duo can be used to deep fill or skim coat concrete walls or ceilings. They **DO NOT** require any additives and can be re-tempered without additional water. They're non-shrinking and can be sanded.

Best of all they're from ARDEX, so you can be assured of high-performance and outstanding quality!

ARDEX TWP™

Tilt Wall Patch - for smaller jobs

- High yield up to 150 sq. ft./10 lb. bag
- Fast-drying, hardens quickly
- No additives required
- Deep fill or skimcoat
- Non-shrinking and sandable
- Re-tempers without additional water
- Paintable in 15 to 60 minutes

ARDEX OVP™

Overhead Vertical Patch – for larger jobs

- High yield up to 300 sq. ft./20 lb. bag
- Extended pot life and working time
- No additives required
- Deep fill or skimcoat
- Non-shrinking and sandable
- Re-tempers without additional water
- Paintable in 2 to 3 hours



EXTERIOR CONCRETE RESTORATION & REPAIR

Repair and resurface damaged concrete surfaces such as parking decks, sidewalks, driveways and walls. Freeze/thaw resistant.	Wear surface	Max. installation thickness without aggregate	Max. installation thickness with aggregate	Working time	Sandable	Compressive strength psi (ASTM C109/mod air cure only)	Portland cement-based	Water resistant	Self-drying	Recommended sealer or topping	Curing time before painting or sealing
ARDEX K 301™ EXTERIOR SELF- LEVELING TOPPING For restoration of outdoor concrete surfaces.	•	3/4"	2"	10 min.	N/A	4300	•	•	N/A	ARDEX CG™	24 hrs
ARDEX CPTM CONCRETE PATCH Cementitious topping for filling and repairing outdoor and indoor concrete.	•	1/2"	1"	30-45 min.	N/A	3600	•	•	N/A	ARDEX CG™	24 hrs
										ARDEX CD™ or CD FINE™	4 hrs
ARDEX CD TM / ARDEX CD FINE TM CONCRETE DRESSING No primers or pre-wetting necessary before applying. Easily applied by trowel or squeegee.	•	1/4"	N/A	10-15 min.	N/A	4000	•	•	N/A	ARDEX CG™	when hard (2-3 hrs)
ARDEX TWP™ FINISHING COMPOUND For fast-track, small area repairs of concrete walls. High-yield that dries quickly.	N/A	unlimited (in well defined areas)	N/A	15-20 min.	YES	N/A	•	•	•	ARDEX CG™	when hard (½ hr)
ARDEX OVP™ FINISHING COMPOUND For large area repairs of overhead and vertical concrete. Long pot life with high-yield.	N/A	unlimited (in well defined areas)	N/A	90 min.	YES	N/A	•	•	•	ARDEX CG™	when hard (2-3 hrs)



400 Ardex Park Drive

Aliquippa, PA 15001

Tel: 724-203-5000

Toll Free: 888-512-7339

Fax: 724-203-5001

www.ardex.com

Don't replace the slab...restore it with ARDEX and save time, money and hassle!