

SJE MILLIAMPMASTM Control Switch

Mechanically-activated control switch designed to activate low current control panels and alarms.

This wide-angle or narrow-angle control switch offers reliable low current control for AC and DC applications in potable water, wastewater, and sewage. The internal switching mechanism has sealed gold cross-point contacts for reliable low current operation. Common applications include PLC (programmable logic controller) panels, IS panels with intrinsically safe barriers, low current solar applications, and other low current control panels and alarms applications.

The wide-angle version activates/deactivates approximately 4" above and below horizontal with a 3.5" tether. The narrow angle version activates/deactivates at approximately 1.5" above and below horizontal with a 3.5" tether.

Normally Open Model (high level)

The control switch turns on (closes) when the float tips **above** horizontal signaling a high level, and turns off (opens) when the float drops below horizontal.

Normally Closed Model (low level)

The control switch turns on (closes) when the float drops **below** horizontal signaling a low level, and turns off (opens) when the float tips above horizontal.

FEATURES

- Passed NSF Standard 61 protocol by an approved Water Quality Association laboratory.
- Low current, non-arching applications down to 0.160 mA at 125 VAC.
- Mechanically-activated, snap action contacts.
- High impact, corrosion resistant polypropylene float housing.
- Not sensitive to rotation.
- UL Listed for use in non-potable water and sewage.
- CSA Certified.
- Three-year limited warranty.



SPECIFICATIONS

CABLE: flexible 18 gauge, 2 conductor (UL,CSA) SJOW, water-resistant (CPE) jacket

FLOAT: 2.74 inch diameter x 4.83 inch long (7.0 cm x 12.3 cm), high-impact, corrosion resistant, polypropylene housing for use in sewage and water up to 140°F (60°C)

MAXIMUM WATER DEPTH: 30 feet (9 meters), 13 psi

ELECTRICAL:

125 VAC

Maximum Electrical Load: 0.1 amps

Minimum Electrical Load: 0.160 milliamps

30 VDC

Maximum Electrical Load: 0.1 amps

Minimum Electrical Load: 0.160 milliamps

5VDC

Minimum Electrical Load: 1 milliamps

CONTROL SWITCHES
(MECHANICAL)

OPTIONS

This switch is available:

- for normally open (high level) applications or normally closed (low level) applications.
- with narrow or wide-angle pumping ranges.
- in standard cable lengths of 10, 15, 20, or 30 feet.
- with two mounting options that allow for flexibility in installation:

Mounting Clamp: for applications where the switch can be attached to a discharge pipe or similar mounting device.

Externally Weighted: for applications where the switch can be suspended from above.



PO Box 1708, Detroit Lakes, MN 56502
1-888-DIAL-SJE • 1-218-847-1317
1-218-847-4617 Fax
email: sje@sjerhombus.com
www.sjerhombus.com

SJE MILLIAMPMASTER™ Control Switch

Mechanically-activated control switch designed to activate low current control panels and alarms.

PRICING/ORDERING INFORMATION

Narrow-Angle Versions

Normally Open		Normally Closed		Suggested List Price	Shipping Weight
Part #	Description	Part #	Description		
1018838	10MANPCNO	1018839	10MANPCNC	\$31.27	1.04 lbs.
1018840	10MANWENO	1018841	10MANWENC	\$37.10	2.73 lbs.
1018842	15MANPCNO	1018843	15MANPCNC	\$33.71	1.37 lbs.
1018844	15MANWENO	1018845	15MANWENC	\$39.54	3.05 lbs.
1018846	20MANPCNO	1018847	20MANPCNC	\$36.15	1.69 lbs.
1018848	20MANWENO	1018849	20MANWENC	\$41.98	3.30 lbs.
1018850	30MANPCNO	1018851	30MANPCNC	\$41.45	2.34 lbs.
1018852	30MANWENO	1018853	30MANWENC	\$47.28	4.03 lbs.

Wide-Angle Versions

Normally Open		Normally Closed		Suggested List Price	Shipping Weight
Part #	Description	Part #	Description		
1015725	10MAPCNO	1016180	10MAPCNC	\$31.27	1.04 lbs.
1016181	10MAWENO	1016182	10MAWENC	\$37.10	2.73 lbs.
1016184	15MAPCNO	1016185	15MAPCNC	\$33.71	1.37 lbs.
1016186	15MAWENO	1016187	15MAWENC	\$39.54	3.05 lbs.
1016211	20MAPCNO	1016212	20MAPCNC	\$36.15	1.69 lbs.
1016213	20MAWENO	1016214	20MAWENC	\$41.98	3.30 lbs.
1016215	30MAPCNO	1016216	30MAPCNC	\$41.45	2.34 lbs.
1016217	30MAWENO	1016218	30MAWENC	\$47.28	4.03 lbs.

PC = Pipe Clamp WE = Weighted Externally NO = Normally Open NC = Normally Closed

NOTE: Descriptions are grouped by cable length measured in feet (10, 15, 20, 30)

SPECIFICATIONS

CABLE: flexible 18 gauge, 2 conductor (UL, CSA) SJOW, water-resistant (CPE) jacket

FLOAT: 2.74 inch diameter x 4.83 inch long (7.0 cm x 12.3 cm), high impact, corrosion resistant, polypropylene housing for use in sewage and water up to 140°F (60°C)

MAXIMUM WATER DEPTH: 30 feet (9 meters), 13 psi

ELECTRICAL:

125 VAC

Maximum Electrical Load:
0.1 amps

Minimum Electrical Load:
0.160 milliamps

30 VDC

Maximum Electrical Load:
0.1 amps

Minimum Electrical Load:
0.160 milliamps

5 VDC

Minimum Electrical Load:
1 milliamps

OPTIONS

PACKAGING

Bagged - Standard
Boxed - Specify and add \$1.80 to list price.

Bulk - Specify and deduct 20¢ from list price.

No Mounting - deduct 60¢ from mounting clamp list price.

ADDITIONAL CABLE

Additional cable length over 30 feet is available at 70¢ per foot (list price).

UL Listed for Water & Sewage



Passed NSF standard 61 protocol by an approved Water Quality Association laboratory.



OTHER INFORMATION

NORMALLY OPEN (HIGH LEVEL) OPERATION

The control switch closes (turns on) when the float tips **above** horizontal signaling a high level, and opens (turns off) when the float drops **below** normal.

NORMALLY CLOSED (LOW LEVEL) OPERATION

The control switch closes (turns on) when the float drops **below** horizontal signaling a low level, and opens (turns off) when the float tips **above** horizontal.



www.sjrhombus.com
sje@sjrhombus.com

Call or fax your order!

1-888-DIAL-SJE (1-888-342-5753) ■ Fax 218-847-4617