

# TANK ALERT® XT Alarm System

## Versatile, indoor or outdoor liquid level alarm system.

This alarm system monitors liquid levels in lift pump chambers, sump pump basins, holding tanks, sewage, agricultural, and other non-potable water applications.

The **Tank Alert® XT** indoor/outdoor alarm can serve as a high or low level alarm depending on the float switch model used.

The alarm horn sounds and the red beacon illuminates when a potentially threatening liquid level condition occurs. A "power on" light on the switch indicates power to the alarm panel.



## FEATURES

- Enclosure meets Type 3R water-tight standard.
- Automatic alarm reset, horn silence switch, and alarm test switch.
- Alarm horn sounds at 85 decibels at 10 feet (3 meters).
- Alarm system (when installed on separate circuit) operates even if pump circuit fails.
- Complete package includes standard SJE SignalMaster® control switch with 15 feet (4.57 meters) of cable (other lengths available) and mounting clamp.
- UL Listed for indoor or outdoor use.
- CSA Certified.
- Three-year limited warranty.



## OPTIONS

### When ordered with the alarm, the system is available with:

- alternate float switch models for high or low liquid level warning.
- auxiliary dry normally open contacts for easy attachment of remote devices.
- premounted terminal block so enclosure can also be used as a junction box for splicing pump, pump switch, and pump power. Meets NEC standard for junction boxes.
- 6 foot (1.8 meter) power cord and liquid-tight connectors.

## SPECIFICATIONS

**VOLTAGE:** 120 VAC, 50/60 Hz

**ALARM ENCLOSURE:** 6.5 x 4.5 x 3.0 inch (16.51 x 11.43 x 7.62 cm), indoor-outdoor, weatherproof, thermoplastic meets Type 3R water-tight standard

**ALARM HORN:** 85 decibels at 10 feet (3 meters), meets Type 3R water-tight standard as installed by factory

**ALARM BEACON:** UL Listed, Type 4x beacon assembly

**TEST/SILENCE SWITCH:** certified to IP66 and IP68 standards

**AUXILIARY ALARM CONTACTS (OPTIONAL):** 120 VAC, 5 amps max., 50/60 Hz

**PRE-MOUNTED TERMINAL BLOCK (OPTIONAL):** 20 amps, 120/230 VAC

**POWER CORD (OPTIONAL):** 6 foot (1.8 meter) cord with 120 VAC plug

**FLOAT SWITCH:** SJE SignalMaster® control switch with mounting clamp

**Cable:** 15 feet (4.57 meters), flexible 18 gauge, 2 conductor (UL) SJOW, water-resistant (CPE)

**Float:** 2.74 inch diameter x 4.83 inch long (7 cm x 12.3 cm), high impact, corrosion resistant polypropylene housing for use in sewage and non-potable water up to 140°F (60°C)

**Maximum Water Depth:** 30 feet (9 meters), 13 psi

**Electrical:** 5 amps, 125 VAC/250 VAC, 50/60 Hz

**SJE**  
**Rhombus**®

PO Box 1708, Detroit Lakes, MN 56502  
1-888-DIAL-SJE • 1-218-847-1317  
1-218-847-4617 Fax  
email: sje@sjerhombus.com  
**www.sjerhombus.com**