

2x2 DVI DL KVM SWITCHER

Switch between any two dual display computers with support for two dual link DVI, USB 2.0 and audio signals



EXT-DVI-422 DL



FEATURES:

- Switches easily between any two dual display computers with DVI, USB 2.0 and audio
- Supports resolutions up to 3840x2400
- Supports all major operating systems - Windows, MacOS and Linux
- Integrated 2-port USB hub
- Discrete front panel switching
- Discrete IR remote (included)
- Contact closure remote port (RMT-2 not included)
- Discrete switching via integrated RS-232 serial communications
- Supports DDWG standards for DVI monitors
- Rack-mountable

SPECIFICATIONS:

- Maximum Pixel Clock: 2x165 MHz
- Input DDC Signal: 5 Volts p-p (TTL)
- Maximum Resolution: 3840x2400
- DVI Input: (4) DVI-D DL 25 pin female
- DVI Output: (2) DVI-D DL 25 pin female
- Audio Input: (2) 3.5mm mini-stereo jack
- Audio Output: (1) 3.5mm mini-stereo jack
- USB Input Connection: (2) Type B
- USB Output Connection: (2) Type A
- Rack Size: 1U (rack-ears included)
- Power Supply: 5V DC
- Power Consumption: 10 Watts (max)
- Dimensions: 4.2"D x 17.1" W x 1.8"H
- Shipping Weight / Unit Weight: 2 lbs. /8 lbs.



4x4 DVI KVM DL MATRIX

Switch between any four computers, with support for dual link DVI, USB 2.0 and audio, to any four workstations



EXT-DVIKVM-444DL



FEATURES:

- Increases productivity by providing access to four computers from any combination of four workstations
- Supports resolutions up to 3840x2400
- Supports all major operating systems - Windows, MacOS and Linux
- USB 2.0 matrix switching capabilities
- Supports analog audio matrixing
- Discrete IR remote (included)
- Remote switching available using EXT-RMT-MATRIX-444 (sold separately)
- Discrete switching via integrated RS-232 serial communications
- Supports DDWG standards for DVI monitors
- Rack-mountable

SPECIFICATIONS:

- Maximum Pixel Clock: 165 MHz
- Input DDC Signal: 5 Volts p-p (TTL)
- Maximum Resolution: 3840x2400
- DVI Input: (4) DVI-I 29 pin female
- DVI Output: (4) DVI-I 29 pin female
- Audio Input: (4) 3.5mm mini-stereo jack
- Audio Output: (4) 3.5mm mini-stereo jack
- USB Input Connection: (4) Type B
- USB Output Connection: (4) Type A
- Remote Switch Connection: (4) RJ-45 shielded
- Rack Size: 1U (rack-ears included)
- Power Supply: 5V DC
- Power Consumption: 20 Watts (max)
- Dimensions: 4.2"D x 17.1" W x 1.8"H
- Shipping Weight / Unit Weight: 2 lbs. /7 lbs.

