



Tired of pulling multiple cables? Fed up with long, bulky cable runs? **Simplify with Intelix DIGI-V3SD extenders.**

When used with a compatible send balun, distribution amplifier, or matrix switcher, the DIGI-V3SD-R transmits component video, stereo audio, IR and RS232 up to 1,000 feet over a single twisted pair cable. Plus, built-in skew correction ensures perfect 1080i, 720p, 480i, and 480p video every time.

No matter the application, the SD Series has you covered.

Maximum Distance	1,000 feet
Supported Signals	YPbPr, Y/C, composite video, stereo audio, IR, RS232
Supported Resolutions	1080i, 720p, 480i, 480p
Video Bandwidth	300 MHz
Audio Frequency Response	20 Hz to 20 kHz
Connectors	(3) RCA: video (2) RCA: audio (1) 1/8" mini: IR (1) DB9: RS232
Enclosure	Metal
Max Distance of AV Cables	6 feet
Skew Adjustment	Front panel (R,G,B) trim pots on the receive unit
Operating Temperature Range	-41 to 95 degrees F -5 to 35 degrees C
Operating Humidity Range	5 to 90% non-condensing

Control	IR and bi-directional RS232
IR Direction	From destination to source
Power	5 VDC
Diagnostic	Power LED
Regulatory	CE, RoHS
Shipping Weight	5.0 lbs
Dimensions	5.25" x 3.38" x 1.00"
Intelix Part Number	DIGI-V3SD-R
Compatible Transmitters	DIGI-V3A2-S DIGI-V3SD-S DIGI-VGASD-8X8 DIGI-VGASD-16X16 DIGI-VGASD-T4 DIGI-VGASD-T8
Included Accessories	(1) 5 VDC power supply
Warranty	2 years

*Note: the DIGI-V3SD-R transmits IR or RS232, not both simultaneously. RS232 takes precedence over IR.

