

## 600A AC True RMS Clamp Meter



- True RMS for the most accurate measurement when harmonics are present.
- AC amperage, AC/DC voltage, frequency and resistance measuring capability.
- Easy-to-read backlit display for use in low light conditions.
- Peak and data hold to capture measurement.
- MIN/MAX feature for added versatility.
- Analog bar graph to view quick changes.
- Selectable Auto Off for longer battery life.
- Accessories included: (1) 9V battery, test leads, carrying case.
- Lifetime Limited Warranty.

CAT. NO.	UPC NO.	DESCRIPTION
CM-850	07666	True RMS Clamp Meter
CM-850-C*	10857*	True RMS Clamp Meter
TLK-1	12035 <b>B</b>	Test Leads

\* Includes Certificate of Calibration  
 Note: See page 358 for replacement case

### SPECIFICATIONS

<b>Amperage Measurement</b>	AC - 400.0, 600A
<b>Voltage Measurement</b>	400.0, 600V
<b>Resistance</b>	400.0Ω
<b>Frequency</b>	0.400kHz
<b>Display</b>	4000-count LCD
<b>Jaw Opening</b>	1.34" (34mm)
<b>Measurement Category</b>	CAT III, 600V

Testing & Measurement



## 600A AC Clamp Meter



- AC amperage, AC/DC voltage, frequency and resistance measuring capability.
- Easy-to-read backlit display for use in low light conditions.
- Peak and data hold to capture measurement.
- MIN/MAX feature for added versatility.
- Analog bar graph to view quick changes.
- Selectable Auto Off for longer battery life.
- Accessories included: (2) 1.5 V AA batteries, test leads, carrying case.
- Lifetime Limited Warranty.

CAT. NO.	UPC NO.	DESCRIPTION
CM-800	07664	Clamp Meter
CM-800-C*	10856*	Clamp Meter
TLK-1	12035 <b>B</b>	Test Leads

\* Includes Certificate of Calibration  
 Note: See page 358 for replacement case

### SPECIFICATIONS

<b>Amperage Measurement</b>	AC - 400.0, 600A
<b>Voltage Measurement</b>	400.0, 600V
<b>Resistance</b>	400.0Ω
<b>Frequency</b>	0.400kHz
<b>Display</b>	4000-count LCD display
<b>Jaw Opening</b>	1.34" (34mm)
<b>Measurement Category</b>	CAT III, 600V

USA Tel: 800.435.0786  
 Fax: 800.451.2632

Canada Tel: 800.435.0786  
 Fax: 800.524.2853

International Tel: +1.815.397.7070  
 Fax: +1.815.397.9247