

Weatherproof Intensifier™ Bullet Cameras

**BEST
SELLER!**

Dark Gray housing

HTINTB8 (2.8-12mm lens)

HTINTB9 (5-50mm lens)

HTINTB10 (9-22mm lens)

White housing

HTINTB8W (2.8-12mm lens)

HTINTB9W (5-50mm lens)

HTINTB10W (9-22mm lens)



**Includes video
test connector**

Intensifier™ Bullet Features

- Amplify existing light with no distance limitations
- No problems caused by objects that reflect or absorb IR light sources
- 580 lines of resolution
- Minimum illumination 0.002 lux (Intensifier™ @ 256x)
- Dual voltage 12V DC & 24V AC operation
- Full OSD operation
- External controls for zoom and focus
- SLC - Speco Light Compensation
- S/N Ratio more than 50dB (weight on)
- Weatherproof operation, IP-67
- EZ mount system simplifies installation
- 5 year warranty


Specifications

Resolution	580 TV line
Intensifier™	Built-in (selectable from 2x to 256x)
Image Device	1/3" Sony Super-HAD™ CCD - 410K*
Minimum Illumination	0.002 lux - Intensifier™ @ 256x
SLC (Speco Light Compensation)	Low, middle, High, Off, Selectable, HLC
White Balance	ATW/AWC/MANUAL (1800K - 10,500K)
S/N Ratio	More than 50dB (weight on)
Video Output	Composite video 1.0 Vp-p into 75 Ohm + test connection
Electronic Shutter	Auto/Manual (1/60 - 1/120,000 seconds)
OSD	Built-in - controlled by internal buttons
Auto Gain	Low, Middle, High, Off, Selectable
Reduce Noise	Low, Middle, High, Off, Selectable
Day & Night (Color)	On / Auto Selectable
Sharpness	On / Off (Level Adjustable)
Privacy	On / Off (4 Programmable Zones)
Power Consumption	210mA
Power Requirements	24 Volts AC, 12 Volts DC - Dual Voltage
Lens	DC Auto Iris Varifocal Lens (2.8-12mm, 5-50mm or 9-22mm)
Total Pixels	811(H) x 508(V)
Effective Pixels	768(H) x 494(V)
Scanning Frequency	15.734kHz(H) / 59.94Hz(V)
Scanning System	2:1 Interlace
Synchronization	Internal / Line lock in 24V AC
Motion Detection	MD1 / MD2 / OFF- Relay outputs
Operating Temperature	-14°F to 122°F - RH 95% Max.
Storage Temperature	-40°F to 140°F - RH 95% Max.
TV System	NTSC
Dimensions	3.94" W x 4.92" H x 8.19" L
Weight	3 lbs.

INTENSIFIER²

*See In The Dark
Without IR LEDs!**

**Includes
EZ Mount
Plate**



**See page 78 for Compatible
Camera Mount Accessories**

*Requires only 0.002 lux

