

The UL listed, 60 Watt PL60SA and 120 watt PL120SA amplifiers offer versatility well beyond the typical 70V mixer amp. With 3 source inputs and 2 zone outputs, they have the capability of sending each source simultaneously or independently to either zone. This is ideal for installations where a particular area may not need to hear a page but should hear music; such as a restaurant or office with public areas. Another important innovation is that the design allows 70V audio to optionally be played in stereo.

These feature-rich amplifiers include (1) XLR microphone connector with priority paging, RCA input terminals, 600 Ohm input for telephone paging, music-on-hold output and a 24V DC input for backup power. The addition of our 5 year warranty displays our leadership in the commercial sound marketplace.



Ideal for Restaurants/Bars, Offices, Entertainment Venues, Residences and much more. Anywhere that requires long wire runs.

60 watt PL60SA

120 watt PL120SA



PL60SA Specifications

- 60 Watts RMS (2 Lines of Speaker Outputs; 30 Watts per channel)
- XLR Connector with priority paging
- Left and right channel pair RCA inputs
- RCA pair output
- 600 Ohm telephone paging input
- Music on Hold feature
- 24V DC battery input for emergency power
- Separate volume controls for auxiliary by each channel
- Master volume and bass and treble controls
- 3.5" H x 16.9" W x 11.6" D
- UL & CSA listed

PL120SA Specifications

- 120 Watts RMS (2 Lines of Speaker Outputs; 60 Watts per channel)
- XLR Connector with priority paging
- Left and right channel pair RCA inputs
- RCA pair output
- 600 Ohm telephone paging input
- Music on Hold feature
- 24V DC battery input for emergency power
- Separate volume controls for auxiliary by each channel
- Master volume and bass and treble controls
- 3.5" H x 16.9" W x 11.6" D
- UL & CSA listed



(rear of unit)