

Indoor Intensifier™ Wall & Ceiling Mount Dome Cameras

INTENSIFIER™ 2

See In The Dark
Without IR LEDs!*



See In The Dark Without IR LEDs!*

CVC6246iHR Black housing
CVC6246iHRW White housing

**Includes video
test connector**

Intensifier™ Series Features

580 Lines of Color Resolution	Extreme resolution for extreme detail
2.8 to 12mm Auto Iris Varifocal Lens	A wider zoom range to fit more applications
Wall & Ceiling Mount	Features an internal 3-axis mount for maximum versatility
Dual Voltage Operation	12 Volts DC or 24 Volts AC with line-lock Voltage is auto-sensing
Warranty5 Years

Specifications

Horizontal Resolution	580 TV lines
Intensifier™	Built-in (selectable from 2x to 256x)
Image Device	SONY HQ-1™ with a customized DSP
Min. Object Illumination	0.002 lux (Intensifier™) 0.03 lux (shutter)
Effective Picture Element	410K
Speco Light Compensation (SLC/WDR)	OFF, LOW, MIDDLE, HIGH/HLC
White Balance	W-ATW / AWC / MANUAL
Video S/N Ratio	Greater than 50db
Electronic Shutter	1/60-1/100,000 seconds
On Screen Display (OSD)	Built-in
AGC	AGC-L, AGC-M, AGC-H, OFF selectable
Built-In Lens	DC auto iris varifocal lens 2.8-12mm, 1:1.3-2.0
Mechanical Construction	Polycarbonate
Video Signal Output	1.0V(p-p) NTSC composite, 75 Ohms / BNC Connector + Video Test Connector
Power Consumption	230mA (DC) / 3.8W (AC)
Power Requirements	12V DC & 24V AC (Dual Voltage)
Scanning System	2:1 interlaced 525 lines / 60 fields / 30 frames
Synchronization	Internal / line lock selectable through OSD
Video Noise Reduction	ON / LOW / MIDDLE / HIGH
Motion Detection	MD1 / MD2 / OFF - Relay out
Privacy function	ON / OFF (4 Programmable Zones)
Operating Environment	14°F to 120°F
Dimensions	5.5" W x 4.5" H
Weight	16 ounces

NEW

**Flush Mount Kit
DFM2**



See pg. 80 for Mounting Accessories: Flush Mount Kit - DFM2
See page 78 for Compatible Camera Mount Accessories



*Requires only 0.002 lux