

High Resolution Color Dome Camera with 2.8-12mm Auto Iris Lens

Resolution	550 lines
Min. Object Illumination	0.3 lux sensitivity
Image Device	1/3" Sony Super-HAD™ CCD
Built In Lens	2.8-12mm F1.4 auto iris lens
Electronic Shutter	1/60-1/100,000 seconds
Synchronization	Internal / line locked in 24V AC mode
Video S/N Ratio	Greater than 48dB
Video Signal Output	Composite Video, 1 Vp-p into 75 ohms, test connection
Power Consumption	300mA (DC) / 4W (AC)
Power Requirements	Dual voltage operation: 12V DC & 24V AC
DIP Switches	BLC, FLK, AGC AND AES/AI
Gamma	0.45
Mechanical Construction	Polycarbonate housing with lined dome cover
Scanning System	525 lines interlaced
Operating Environment	14°F to 122°F
Dimensions	5.5" Dia. x 3.5" H
Weight	12 oz.
Accessories	Wall/ceiling mountable with 3-axis mount & template included



550 Lines Resolution
Wall or Ceiling Mount
Dual Voltage Operation

CVC6146HR

High Resolution Color Dome Camera, 2.8-12mm Auto Iris Lens with Full OSD and 12VDC / 24VAC Dual Voltage Operation

Resolution	550 TV line
Minimum Illumination	0.5 lux
Image Pick-Up Device	1/3" Sony Super-HAD™ CCD
Lens	2.8-12mm auto iris varifocal lens
Effective Pixels	768(H) x 494(V)
Scanning System	2:1 Interlace
Synchronization	Internal
S/N Ratio	More than 50dB
Power Requirements	12 Volts DC Required - Speco PSW5



3 WAY AXIS MOUNT

CVC6146SCS
CVC6146SCSW

Indoor Dome with 2.8-12mm lens

See pg. 42 for our full line of On Screen Display Models
 See page 78 for Compatible Camera Mount Accessories

Dome Flush Mount Kit

- Back box easily flush mounts into hollow walls and ceilings.
- Flush mount box is secured with the use of four EZ mount retaining clamps.
- Perfect for existing construction.
- Preconfigured to fit several types of Speco tamperproof and indoor dome cameras



DFM2 & DFM3

See pg. 80 for more information