

NEXUS™ UL® Contractor Series Speakers



Speco Technologies' Nexus Contractor Speakers Commercial Line utilizes premium quality components to provide a network of sound and paging for even the most demanding commercial environments.

The high-end NXC Series features heavy-duty, industrial metal back cans that provide component protection and safety while enhancing the speakers' full-range bass sound. Removable "Quick-Snap" connection terminals provide easy access and optimal angles for connecting speaker wire. A wattage selector dial simplifies transformer settings. Mounted security loops allow for a support cable run and ceiling support brackets are included.

Most importantly, these speakers have met or passed the strict UL 1480 requirements for fire safety.

NEW

N | E | X | U | S
Contractor Series



SP6NXCTUL

6.5" Metal Back Can 70V Speaker

6.5" Polypropylene Woofer w/Rubber Surround

¾" Silk Dome Tweeter

Frequency Response: 60Hz to 20kHz

Sensitivity: 87db 1w/1m

Impedance: 8 Ohms

Max power handling: 80W

70V Transformer Switch

Transformer settings: 30W, 15W, 7.5W, 3.7W & 1.9W

Dimensions: 10.25" Diameter x 7.75" Depth

Cut Out Dimensions: 8.75"

Quick-Snap terminal connections

UL 1480 Rated


Metal Safety Loop for Securing

Mounting Brackets Included

Sold in Pairs




Fire retardant metal back can




Mounting brackets included



Quick-snap terminal connects



Safety loop



Transformer dial



Ported bass