



LibertyLinx™ Universal Control Cables

One of the main components of the Liberty Advantage is our ability to bring new, cutting edge products to the market. Our LibertyLinx product

offering provides the AV professional with a greater selection of proven control solutions keeping you both competitive and profitable.

LibertyLinx™-QM-Plenum Control Cable								
<p>LibertyLinx-STD Component Low Skew Cat 5e Component</p> <p>Equal to Crestron Part #: crescat-qm-p Equal to Isotec Part #: 18/22QMP</p>	Description	Shield	NOM Insulation (Inches)	NOM Jacket (Inches)	NOM OD (Inches)	NOM Capacitance (pF/ft)	Color Code	Part #
		LibertyLinx™ + TRUphase™ Low-Skew						
Element 1								
	22 AWG 1 PR STR BC (7x30)	Foil+ 24 AWG STR TC Drain	.025 FFEP	N/A	N/A	12.5	Blue White	Data
	18 AWG 2C STR BC (16x30)	N/A	.009 PLN-PVC	N/A	N/A	N/A	Red Black	Power
Element 2								
	24 AWG 4 PR Solid BC	N/A	.007 PLN-TPE	N/A	N/A	17		Low-Skew CAT5 UTP
Overall Construction								
				.025	.200x.400			Overall Siamesed Plenum Rated Jacket

Also available in PVC: Part #: LibertyLinx™-QM

LibertyLinx™ Specialized Control Cable							
<p>Cat5e Component Outer Jacket RG59/U SD Coax Component 18 AWG LoCap Pair Component</p>	# of Conductors	AWG Size/ Stranding	Shield	NOM Insulation (Inches)	NOM Jacket (Inches)	NOM OD (Inches)	Part #
CONSTRUCTION							
	4 (2 pair)	18 AWG STR TC (7x26)	Overall AL Poly w/ 20 AWG STR TC Drain	0.020 FPE	0.030 FR-PVC	0.250	Control Pair Shielded Low Cap
	1	20 AWG Solid BC	100% Foil+ 95% TC Braid	0.145 FPE	0.032 FR-PVC	.240	RG59 Serial Digital Coax
	8 (4 pair)	24 AWG Solid BC	N/A	0.008 PE	0.021 FR-PVC	0.205	Enhanced Cat 5e
					0.045 PVC	.650	Overall Construction

LibertyLinx™ Specialized Control Cable							
<p>Cat5e Component Outer Jacket RG6/USD Coax Component 18 AWG LoCap Pair Component</p>	# of Conductors	AWG Size/ Stranding	Shield	NOM Insulation (Inches)	NOM Jacket (Inches)	NOM OD (Inches)	Part #
CONSTRUCTION							
	4 (2 pair)	18 AWG STR TC (7x26)	Overall AL Poly w/ 20 AWG STR TC Drain	0.020 FPE	0.030 FR-PVC	0.250	Control Pair Shielded Low Cap
	1	18 AWG Solid BC	100% Foil+ 95% TC Braid	0.145 FPE	0.032 FR-PVC	.272	RG6 Serial Digital Coax
	8 (4 pair)	24 AWG Solid BC	N/A	0.008 PE	0.021 FR-PVC	0.205	Enhanced Cat 5e
					0.045 PVC	.650	Overall Construction

With RG6 SD Coax

Specifications Subject to Change

800-530-8998

PERFORMANCE. SELECTION. VALUE.
ORDER TODAY!

LIBERTYLINX™