

Vandalproof Standard Resolution Weatherproof Color Dome Camera with IR LEDs

VL650IRS (silver housing, fixed lens)

VL650IRW (white housing, fixed lens)

VL650IRVFS (silver housing, varifocal lens)

VL650IRVFW (white housing, varifocal lens)



Includes video test connector

Features

- Internal IR LEDs with anti-reflective technology
- Up to 60 ft. IR range using 22 IR LEDs
- Tamper resistant construction
- IP67 rated for extreme weather applications
- Optional wall, ceiling & junction box adapters are available
- Available in white & silver housings
- Multi-function dip switches for precise camera adjustment
- 5 year warranty

Specifications

CCD	.1/3" SONY Super-HAD™ CCD
Resolution	.420 Lines
Lens	VL650IR: 3.6mm board lens VL650IRVF 2.8-12mm F1.4 varifocal auto iris lens
Min. Illumination	.0 Lux (up to 60 ft. range) with LED on, 0.5 Lux with LED off
Number of Pixels	.510 H x 492 V
Cell size	.9.6µm H x 7.5µm V
TV Type	.NTSC
Sync Type	.Internal
Scanning System	.2:1 Interlace
Video Output	.1.0 Vp-p (sync negative) into 75 ohms
Video Test Output	.Cable included
Gamma Characteristic	.γ=0.45 type.
S/N Ratio	.48dB or more (AGC off)
Gain Control	.Automatic
Electronic Shutter	.1/60 Sec to 1/100,000 Sec
AG	.ON/OFF
BLC	.ON/OFF
Flickerless	.ON/OFF
Mirror	.ON/OFF
Test Illuminance Area	.Average test illuminance by front view
Power Requirement	.Regulated 12V DC power supply included
Consumption Current	.Max. 360mA
Reverse Polarity Protection	.YES
Operating Temperature	.-20 °F to 120 °F
Dimensions	.6" Dia. x 3.75"H



Available 650 Series Mounting Accessories, Choose from Silver or White

650WMT
Wall Mount



650CP-Corner/Pole
Mount



650 CMT
Ceiling Mount



650JMT
Junction Box



* Straps required when used as a pole mount. See pg. 79