## a-live<sup>™</sup> Multi-Room 70/25 Volt Audio System

**speco** technologies



a-live allows you to play networked digital music directly from your PC to any and all zones. Streamed audio files can be played from the same playlist simultaneously among different zones. For example, if a user is in zone one, and selects a particular song to start playing, a different user in any of the other zones can select the same exact song to play, from the beginning, without interfering with the current play in zone one. Or they could choose to play a completely different song, and aren't limited by having to share a source unit such as an MP3 player or CD player. Most major unprotected formats are supported.

An intuitive GUI interface allows you to remotely program and control any zone from a PC, and also turns a laptop on the same network with wireless LAN capabilities into a master remote control!

ΑΚΡΑ LCD Keypad

Optional a-live interactive keypads come with 1" blue backlit LCD screens to provide you total zone control, including volume controls w/ mute, tone controls, and full control of all PC-based music including forward, back, pause and scrolling information of artist and song name. Keypads also have IR remote control pass through capability for external source devices such as CD players, home theater audio, etc.



speco technologies

## A6X6A70

Distortion:

Power rating:

Dimensions:

Weight:

Fuse rating

(8 Ohm version on page 43)	
Audio source inputs:	6
Zones per unit:	6
Multiple server management on LAN:	Yes
Keypad ports:	RS-422
Interface ports:	RJ-45 for 100Mbps LAN(Ethernet) RS-232 for system diagnostics
Source input connectors:	RCA jacks (left and right)
Source input impedance:	50k ohm
Source input level:	2.2 Vrms max
Amplifier channels:	6 channels 70/25V

a-live

6 channels 70/25V 20 watts per 70/25V zone Power output: Frequency response: ..... 20 Hz to 20 kHz +0/–2.5 dB >90 dB A-weighted, >88 dB unweighted Signal-to-noise ratio: Speaker impedance (Nominal, minimum): ..... 8 ohms nominal, 6 ohms minimum (8 ohm) Speaker connectors: Removable 4-pole coded snap Audio line outputs: 2.2Vrms (Fixed) Line output connectors: RCA jacks (2 per zone – L/R for 8 ohm module, 2 mono for 75/20V module) 100-120V AC 3A or 220-240V AC 1.25A, 50-60Hz F3.0A H 250V USA and Canada Compatible audio file formats ... MP3, M4A, M4B WPL, XML Compatible audio playlist formats . Pentium 4 3.0+ processor for up to 4-zone digital Minimum system requirements streaming. Pentium dual core 1.60+ processor for up to 6-zone digital streaming Operating system for Manager Windows XP (Service Pack 2) or Windows Vista 512MB Minimum system memory Minimum hard drive space 1GB

34 lbs.



## Live, Networked Audio Streaming **Directly From Your PC or Laptop**

- 70/25V Model Allows For More **Speakers To Be Run Greater Distances** Than The Standard 8 Ohm Outputs
- Allow For Control of Up To 6 Zones Per Unit Through PC/Laptop Interface or Interactive LCD Keypads

## www.specotech.com - 1.800.645.5516

14

17" W x 17.4" L x 3.5" H