15, 30, 60 or 120 Watt Contractor Series Amplifiers



Speco Technologies' UL-listed **Contractor PBM Series** commercial amplifiers offer a reliable and cost-efficient solution for a wide range of applications.

Each amplifier in this series features multiple microphone inputs, an auxiliary input and a 600-Ohm telephone connection for phone paging. This helps to provide the flexibility of sound selection that installers require.

Speaker output terminals of 70 or 25 volt or 4, 8 and 16 Ohms complement higher-end features such as 'Music-on-Hold' and priority paging that are usually not found on amplifiers of this price point.



Ideal for a diverse array of applications

60 watts PBM60 120 watts PBM120



15 OR 30 WATT RMS P.A. AMPLIFIER

- Two MIC inputs (terminal strip)
- Aux input
- Front panel level controls
- Auto mute function
- · Bass and treble tone controls
- Outputs 70/25V and 4/8/16 Ohms
- · Auto summing stereo AUX input
- Music on hold output with separate level control (600 Ohms line and one Watt 8 Ohms)
- 600 Ohms tel. line input with level control
- · Manual muting contacts
- Accessory AC outlet
- UL & CSA listed

Rack mounting kit available: PBMRK1

60 OR 120 WATT RMS P.A. AMPLIFIER

- Three MIC inputs (terminal strip)
- 1 XLR connector
- · Aux input
- Front panel level controls
- Auto mute function
- Bass/treble tone controls
- Outputs 70/25V and 4/8/16 Ohms
- Auto summing stereo AUX input
- Music-on-hold output with separate level control (600 Ohms line and one Watt 8 Ohms)
- 600 Ohms tel. line input with level control
- Manual muting contacts
- Accessory AC outlet
- UL & CSA listed

Rack mounting kit available: PBMRK2

ltem	MIC Inputs	XLR MIC Inputs	AUX Inputs	Telephone Paging	70/25 Volt	Music-on-Hold	Aux. Output	Bass/Treble Controls		Measurements
PBM15	2		1	√	√	✓		7	Π	10 3/4" W x 3 1/2" H x 9 1/2" D
PBM30	2		1	√	√	√		7	I	10 3/4" W x 3 1/2" H x 9 1/2" D
PBM60	3	1	1	1	√	√	1		/ T	17" W x 3 3/4" H x 11 1/4" D
PBM120	3	1	1	√	 √	√	1		Π	17"W x 3 3/4" H x 11 1/4" D