

Gorilla Sleeve Metal Braid



- Flat Filament Technology
- Heavy Plastic Protection
- Smooth Feel & Reduced Drag

Innovative Flat Filament Braided For High Abrasion Resistance

The latest innovation in Techflex material design is the concept of using different shaped filaments to create strength, stiffness or a variety of other effects. Gorilla Sleeve utilizes flat filaments to achieve a thick abrasion guard for use on hoses. This type of sleeve has been tested against competitor's abrasion guards that mix materials in an effort to gain slight abrasion advantages. Gorilla Sleeve achieves better results without sacrificing great looks or flexibility. Contact your Account Representative for additional information on available styles of Gorilla braid for your application.



Constant abuse from road hazards, abrasion and vibration make Gorilla Sleeve the choice to protect hoses in over the road vehicles.

Nominal Size	Part #	Expansion Range		Standard Spool Put-Ups		Available Colors	Lbs/100'
		Min.	Max.	Bulk Spool	Mini Spool		
1/2"	NHN0.50	3/8"	5/8"	500'	100'	Black	1.4
3/4"	NHN0.75	5/8"	1"	250'	50'	Black	2.1
1 1/4"	NHN1.25	1"	1 1/2"	250'	50'	Black	2.5
1 3/4"	NHN1.75	1 1/2"	2"	100'	25'	Black	4.0



- EMI, RFI, ESD Protection
- Grounding Straps
- Engine Dress-Up
- Military Applications
- Extreme Blowout Protection
- Expands For Easy Installation

Tinned Copper Sleeve For Shielding, Grounding And Decoration



Our skill with braided sleeving extends to many materials including metal braid for a variety of applications. Our tinned copper braid is perfect for shielding on harnesses and cables. Wire conforms to ASTM-B 33.

The material is also great for hose covering on hot rods and motorcycles.



High end automotive applications have always used metal braided onto hoses for looks, protection and durability.

Nominal Size	Part #	AWG of Ends		Wires per Carrier	Current Capacity Amps	Standard Spool Put-Ups		Available Colors	Lbs/100'
		Carriers	Carriers			Bulk Spool	Mini Spool		
5/32"	MBN0.16	36	24	10	40.0	250'	100'	Silver	2.1
1/4"	MBN0.25	36	24	16	53.0	250'	100'	Silver	2.2
3/8"	MBN0.38	36	48	8	53.0	250'	100'	Silver	3.3
1/2"	MBN0.50	30	24	15	120.0	100'	50'	Silver	12.0
5/8"	MBN0.63	36	48	15	70.0	100'	50'	Silver	3.6
25/32"	MBN0.78	36	48	18	88.0	100'	50'	Silver	7.35
7/8"	MBN0.88	30	48	7	100.0	100'	50'	Silver	10.3
1"	MBN1.00	30	48	8	120.0	100'	50'	Silver	13.15
1 1/2"	MBN1.50	30	48	12	145.0	100'	50'	Silver	18.4
2 1/4"	MBN2.25	30	48	16	190.0	100'	50'	Silver	23.6