

IP Server and Intensifier™ In the Camera! Access All Intensifier™ & WDR Functions Over the Internet or Network!

Ideal for Mid-Size Systems with Self-Contained Powerful NVR Software

- Built-in web server works with Internet Explorer; no special software required for basic functionality and recording
- Linux Operating System built into camera – No virus threats
- Free DDNS Server includes storage of up to 30 alarm events
- Dual Streaming (2 data compression): Cameras have both MPEG-4 and JPEGCODECS which allow you to choose between streaming or high quality video
- Analog composite video output for local viewing
- Changeable/Selectable Ports allow one IP address to handle multiple cameras
- Premium NVR software supplied at no extra cost for accessing advanced features
- Remotely view up to 16 cameras in one window - 30 groups of cameras available for a total of 480 cameras
- Support of Dynamic and Static IP addresses
- Multiple levels of password protected remote access
- Includes advanced IP locator software to make system setup easy
- Built in video motion detection
- Multiple alarm handling capabilities: alarm inputs, relay outputs
- Remotely upgradeable for software and firmware functions
- Schedule recording, per camera, per day, per hour - separate schedules for regular, motion and alarm settings
- Selectable Resolutions: 704 x 480, 352 x 480, 352 x 240
- Protocols: HTTP, FTP, TCP/IP, DHCP, ARP, DNS, ICMP, DDNS
- Up to 50 simultaneous users
- 5 Year warranty

See page 78 for Compatible Camera Mount Accessories



IPSD10X

IP/Network Intensifier™ Speed Dome Camera

- Weatherproof/Tamper resistant
- 10x Optical Zoom 3.8mm-38mm
- 10x Digital Zoom
- 150° Per Second Movement
- Indoor/Outdoor Use
- Intensifier™ Functions
- True Day/Night Operation



WMSD10X
Wall Mount
(Sold Separately)



CPSD10X
Corner/Pole
(Sold Separately)

Weatherproof Tamperproof



IPINTD3
2.8-11mm
Auto Iris Dome Camera

IPINTD4
5-50mm
Auto Iris Dome Camera

Traditional



IPINTT5
Traditional Camera
Uses C/CS Lenses

IPT5
No Intensifier Feature

WDR/IP Wide Dynamic Range

For Your Toughest Lighting Situations!



Includes video test connector



IPWDRB1
2.8-11mm
Auto Iris Bullet Camera

Features PIXIM
wide dynamic range
technology. See pg 35

Power Over Ethernet



IPPOEH101

IPPOECAM

- Power any Speco Technologies IP Camera from up to 330 ft. away
- Does not limit camera performance or features

IP/Network Decoder



Front

IPD101

Rear

- Receives protocol "C" network transmission and converts them to analog signals

IP/Network Video Server

- Allows any analog CCTV camera to function as a Speco Technologies IP Camera



Front

Rear

IPS101

- Supports 2-way audio when paired with a microphone, amplifier and speaker

