

Color Four Wire Video Security Intercom System

Our two-way video security intercom system has a flat 4" screen. It offers a two way manual switcher, a 165 foot maximum wiring distance and can be used with an optional door release. The manual switcher allows the system to be expandable up to 2 monitors and 2 cameras. The system comes with an outdoor flush mount camera.

VDP6000
Color System



extra surface mount color monitor
VDPM6F

Specifications

	VDPM6F (Color Monitor)	VDPC6F (Flush Mount Color Camera)
Angle of Picture	N/A	Horizontal: 110° - Vertical 92°
Call Signal Device	Door chime	Push button
Communication System	Duplex handset	Duplex hands free conversation
Connection	Screw terminals DIN connector	Screw terminals
Dimension	8-1/4"(H) x 7-1/2"(W) x 2-1/3"(D)	7-1/4"(H) x 4-3/4"(W) x 3/4"(D)
Housing	White ABS plastic	Pewter gray metal
Illumination	LCD backlit	Infrared LED's
Lens	N/A	3.6mm
Max Wiring Distance	165' (22AWG wire)	165' (22AWG wire)
Minimum Illumination	N/A	0.1 lux on object up to 19 feet
Monitor	4" Flat B/W CRT	N/A
Operating Temp	14°F to 104°F	-4°F to 122°F
Output Impedance	N/A	Video 300 ohm - Audio 600 ohm
Power Source	Regulated 12V DC, (power supply included)	Power supplied from monitor
Scanning Frequency	Horizontal: 15.75 KHz, Vertical: 60Hz	Horizontal: 15.75 KHz, Vertical: 60Hz
Weight	2.86 lbs.	1.1 lbs.
Wiring	4 Wires, 22 gauge minimum	4 Wires, 22 gauge minimum
Relay Output	N.O.	For remote access

Video Security Intercom System - Outdoor Camera

- Infrared LED viewing for night illumination • 3.6mm wide angle lens • Weatherproof camera with aluminum die cast cover
- Sensitive condenser microphone receives outside audio • Tamperproof screws • Angle control allows for adjustment of camera lens angle • Call button activates monitor and chime showing picture of the caller automatically

Surface mount color camera (Dimensions: 1.6"D x 3.5"W x 4.75"H) **VDPC6S**
 Flush mount color camera (Dimensions: 2"D x 4.75"W x 7.25"H) **VDPC6F**