



**CVC6705SCS**  
Weatherproof bullet with  
4-9mm varifocal lens



**CVC700VFSCS**  
Miniature Indoor Color  
Board Camera



**LO**

**CVC6700SCS**  
Weatherproof bullet  
with 6mm lens



See pg. 81 for  
Mounting  
Accessory: Flush  
Mount Kit - DFM2

**Includes video  
test connector**

**CVC6146SCS**  
**CVC6146SCSW**  
Indoor Dome with 2.8-12mm lens  
12VDC / 24VAC Dual Voltage Operation



**LO**

**CVC700HRSCS**  
Miniature with  
4mm board lens



**CVC627SCS**  
Weatherproof bullet with  
IR LEDs & 6mm lens



**Includes video  
test connector**

## Weatherproof OSD Camera with IR LEDs & Varifocal Lens

- 540 TV Lines
- Third Generation DSP Chip
- 1/3" Sony Super HAD CCD™
- True Day/Night  
(ICR-IR Cut Filter Removable)
- 2.8-12mm Auto Iris Varifocal Lens
- External Control Rings for  
EZ Focus and Distance Adjustment
- 12V DC/24V AC Dual voltage operation
- EZ Mount Bracket

**CVC627VFSCS**  
Weatherproof Bullet with 2.8-12mm lens



**CVC770PHSCS**  
Miniature with 3.7mm  
conical pinhole lens

## Full OSD control of all major camera functions:

- Lens** – Controls the brightness of the auto iris lens
- Exposure** – Control Shutter Speed, AGC, Back Light Compensation and Wide Dynamic Range
- White Balance** – ATW, Outdoor, Indoor, Manual, AWC and AWB
- Day/Night** – Select Color, B/W or Auto Select
- S-DNR** – Speco Dynamic Noise Reduction
- Camera Titles** – Up to 15 Characters
- Mirror Image** – Horizontal and Vertical
- Digital Zoom** – Up to 10X
- Privacy Screens** – Up to 8 Zones

**All cameras include mounting brackets**

## Specifications

<b>Resolution</b> . . . . .	540 TV line
<b>Image Pick-Up Device</b> . . . . .	1/3" Sony Super-HAD™ CCD
<b>Effective Pixels</b> . . . . .	768(H) x 494(V)
<b>Minimum Illumination</b> . . . . .	0.5 lux
<b>Scanning System</b> . . . . .	2:1 Interlace
<b>Synchronization</b> . . . . .	Internal
<b>S/N Ratio</b> . . . . .	More than 50dB
<b>Power Requirements</b> . . . . .	12 Volts DC Required- Speco PSW5

