



# 260-9S & 260-9SP Industrial Safety VOM

The new 260 Volt-Ohm-Meter is suitable for testing most commercial and industrial installations and is rated for Category III-600V applications.

Safety is the major design feature of the 260-9S/9SP and the reputation, advantages and reliability of Simpson test equipment is guaranteed.

- Certified to EN61010-1 to 600V, Category III for safety
- Self-contained AC current measurement up to 10 Amps
- Overload protection available
- Includes test lead set with retractable banana jacks and carrying case



## Specifications

### DC VOLTAGE

Ranges	Accuracy	Sensitivity
250mV, 2.5V, 10V, 25V, 60V, 100V, 250V, 600V	2% of full scale	20K $\Omega$ per volt

### AC VOLTAGE

Ranges	Accuracy	Voltage Drop
2.5V, 10V, 25V, 60V, 100V, 250V, 600V	3% of full scale	5K $\Omega$ per volt

### AC CURRENT

Ranges	Accuracy	Sensitivity
0-10	3% of full scale	250mV

Ranges: Up to 250 amperes with AC Amp-Clamp Adapter Accessory #00541

### DECIBEL

5 Ranges: -20 to +43dB

Reference: 0dB= 1mW into 600 $\Omega$

## Specifications (Continued)

### DC CURRENT

Ranges	Accuracy	Voltage Drop: (Nominal)
1mA, 10mA, 100mA, 600mA 10A	$\pm 2\%$ of full scale	250mV

### RESISTANCE

Ranges	Accuracy	Max. Indication
Rx 1 Rx 100 Rx 10K	Better than $\pm 2.5^\circ$ of arc $\pm 2^\circ$ of arc $\pm 2^\circ$ of arc	0-2K $\Omega$ 0-200K $\Omega$ 0-200M $\Omega$

FUSE: F1 1A, 250V, type 3AG, quick acting Littelfuse® Type 312001; F2 2A, 600V Littelfuse® Type BLS or 2A 600V, Bussman® Type BBS.

BATTERIES: 1.5V D, 9V (Neda No. 13F, 1604A)

PHYSICAL: Dimensions 7"(H)x5.25"(W) x 3.1"(D), (17.78x13.34x7.94cm)

Weight 2.25 lbs. (1.02Kg)

Specifications subject to change without notice.

## Ordering Information

ANALOG MULTIMETERS	Catalog No.	ACCESSORIES	Catalog No.	ACCESSORIES	Catalog No.
260-9S, Safety VOM	12397	Case, Nylon Padded, Safety Orange, 260	00838	150-2 AC Clamp Adapter	00541
260-9SP, Safety VOM, protected with case	12398	Test Lead Set, Retractable Banana, Probe Tip	07546	Clip Set, Alligator, Screw On	00425