

## 9" Multi-Voltage, Multi-Standard Color Monitor

- 9" color flat tube, 500 TV lines
- NTSC/PAL system auto switchable
- With S video composite video input
- Wide range power source (90VAC-260VAC)
- High performance
- Dual comb-filter
- Discrete front controls



**COLOR 9"**

VM905C

## 17" or 21" Color High Resolution Monitor with Audio

- More than 520 CRT line resolution (17")
- More than 450 CRT line resolution (21")
- Convenient front controls
- Rugged metal cabinets
- Looping video input/output
- Hi/Lo impedance switch
- Line level audio capability
- With YC output
- Comb filter for enhanced picture quality
- 15.25"L x 16.5"W x 16.4 (17")
- 19.5"L x 19.25"W x 18"H (21")
- UL listed



**COLOR 21" OR 17"**

VM2105C (21") VM1705C (17")



## Portable CCTV Installation & Test Monitor

- Convenient case with shoulder strap
- Handy compact size and shock resistant
- Built-in rechargeable battery
- Includes battery charger
- TFT LCD panel
- 480 x 234 Resolution
- 350cd Brightness
- 250:1 Contrast ratio
- L/R  $\pm 45^\circ$  U/D: 10°/30° View angle
- NTSC
- Video input 1 Vp-p at 75
- 30 mVp-p ~ 100 mVp-p Audio input
- 0.5 Watts max / 8 Audio output
- Video/Audio connector: RCA W/BNC plug Adapter
- 12V.1.1AH. Rechargeable battery
- 12V DC power supply included
- Power consumption 4.5 watts
- 6"W x 5.1"H x 3"D
- 4.3lbs.



VMS2  
Extra Battery BVMS2

## 2.36" LCD Test Monitor

- 2.36 TFT LCD Screen
- 480 x 243 Resolution
- LED Backlight for Low Power Consumption
- (6) "AA" Batteries Included
- 9-12VDC External Power Supply Can Be Used (not included)
- Loop Through BNC Connections (Auto Terminating)
- Leather Carry Case with Wrist and Shoulder Straps.
- Sunshield Built Into The Case
- NTSC / PAL Dual System Support (Automatically Switches)



VMS4