

CAT5/6/7 HDMI Baluns (1080p/60 up to 150 ft. and 1080i/60 up to 300 ft.) (Over 2 CAT5)



KD-CATHD

NEW

HDMI/DVI to dual CAT5/6/7 Cable Extender

TxRx



Key Features

- › KD-CATHD contains 1 KD-CATHDTX Transmitter Balun and 1 KD-CATHDRX Receiver Balun
- › Supports all SD, HD, and VESA (VGA, SVGA, XGA, WXGA, SXGA, UXGA) resolutions up to 1080p (60Hz & 50Hz)
 - › SD & HD: 480i, 480p, 720p, 1080i, 1080p
 - › VESA / DVI: From 640x480p up to 1920x1200p
- › Full support for HDCP, HDMI 1.3a/b, 12-Bit Deep Color Video
- › Supports lossless compressed digital audio (Dolby® TrueHD, Dolby® Digital Plus and DTS™-HD Master Audio)

Key Benefits

- › Transmits (KD-CATHDTX) and receives (KD-CATHDRX) HDMI 1080p/60 signals up to 150 feet and HDMI 1080p/24, 1080i, 720p signals up to 300 feet over two CAT5/6/7
- › Compatible with all video resolutions
- › Allows extension of HDMI signals distances that standard HDMI cables cannot achieve
- › Enables the use of less expensive CAT5/6/7 UTP cabling for HDMI/DVI signal extension

Specifications


Technical:

- › Inputs: KD-CATHDTX - 1 HDMI connector. KD-CATHDRX - 2 CAT5 IN on RJ45 connectors
- › Outputs: KD-CATHDTX - 2 CAT5 OUT on RJ45 connectors. KD-CATHDRX - 1 HDMI connector
- › Bandwidth: 10.2 Gb/s TMDs bandwidth
- › EQ Adjustments: Auto Adjust
- › Compliance w/ HDMI Standards: Supports HDMI1.3+, HDMI1.2, HDMI1.1, DVI1.1, HDCP, and Audio
- › Link and Range: Single Link: (1080p/60) 12 bit color depth, 1920x1200 max. UTP 140 ft., STP 150 ft.; (1080i/60, 720p, 1080p/24) UTP 280 ft., STP 300 ft.
- › Deep Color Support: Supports Digital Video Formats in Deep Color Mode at up to 12 bits/color
- › Lossless Compressed Digital Audio: Supports lossless compressed digital audio (Dolby® TrueHD, Dolby® Digital Plus and DTS™-HD Master Audio)
- › DDC Signal (Data): Input DDC Signal: 5 Volts p-p (TTL)
- › HDMI Video/Audio Signal: Input Video Signal: 1.2 Volts p-p
- › HDMI Connector: Type A, 19 Pin Female
- › RJ45 Connector: Shielded Link Connector RJ45
- › I2C Communication: EDID and HDCP Transparency from Display to Source
- › Power: External Power Supply. 5V DC / 1A, 110-240 VAC, 50-60 Hz

General

- › Regulation: CE, RoHS, WEEE
- › Rack Mount: Bracket (included)
- › Enclosure: Black Metal
- › Product Dimensions: L = 3.5" W = 1.75" H = 1"
- › Shipping Carton Dimensions: L = 7.5" W = 8.5" H = 2"
- › Product Weight: 1 lb
- › Shipping Weight: 2 lbs
- › Accessories: Mounting Clip, Locking HDMI Cable Clip, UL Certified Power Supplies

System Design Example



→ HDMI/DVI
→ CAT5/6/7