

Miniature Weatherproof/Tamper Resistant High Performance Color Dome Camera with Chameleon™ Cover - Built-In 3-Way Mount Allows For Wall or Ceiling Mount

High Resolution Model with Intensifier™: HT647HRTF

Can withstand hits from a 10lb. sledgehammer!

- 580 line high resolution
- 1/3" Sony HQ-1™ (HT647HRTF)
- 0.002 lux
- 3.6mm wide angle lens coverage - optional lenses available
- 1/60 to 1/100,000 sec.
- 1 Vp-p/75 ohms (BNC connector)
- 0.45 Gamma correction
- 120mA current consumption
- Video S/N ratio more than 50dB
- 12 Volts DC power supply included (UL/CSA listed)
- Operating temperature -14°F to 122°F
- Dimensions 4" Diameter x 2.5" H
- Weight 10.5 oz.

Paintable Chameleon™ Cover

INTENSIFIER²

See In The Dark Without IR LEDs!*



Includes video test connector



See pg. 80 for Mounting Accessory: Flush Mount Kit - DFM2

Miniature Weatherproof/Tamper Resistant High Performance Color Dome Camera with Chameleon™ Cover, Built-In 3-Way Mount Allows For Wall or Ceiling Mount

Standard Resolution CVC647TP

Can withstand hits from a 10lb. sledgehammer!

- 420 lines resolution
- Sony 1/4" Super-HAD™ CCD sensor (CVC647TP)
- 1.0 lux / 0.5 lux, F2.0
- 3.6mm wide angle lens coverage - optional lenses available
- 1/60 to 1/100,000 sec.
- 1 Vp-p/75 ohms (BNC connector)
- 0.45 Gamma correction
- 120mA current consumption
- Video S/N ratio more than 50dB
- 12V DC power supply included (UL/CSA listed)
- Operating temperature -14°F to 122°F
- Dimensions: 4" Diameter x 2.5" H
- Weight 10.5 oz.

Paintable Chameleon™ Cover



Color or B/W Dome Camera with Smoked Dome Housing

CVC645DC
CVC645DCW
CVC185DC

Color version with black housing
Color version with white housing
B/W version

B/W Version 420 line resolution • 0.02 lux • 1/3" CCD format • 3.6mm lens
Color Version 420 line resolution • 0.92 lux • 1/4" CCD format • 2.9mm lens

- Can be rotated 360° • Tilt angle +/- 90° • Built-in electronic shutter
- Video output/BNC • Color domes have built-in test connectors
- Regulated 12V DC power supply (UL & CSA listed) included
- Dimensions: 4" Diameter x 2.5"H



Includes video test connector



*Requires only 0.002 lux



B/W lens options include 2.5mm, 6mm, 8mm, & 12mm. Color lens options include UWA (2.2mm), 3.6mm, 6mm, 8mm, 12mm, & 16mm. Please inquire on specific model availability & pricing.