

## Handheld Dynamic Microphone

- Cardioid polar pattern
- Crisp, clear tone quality
- Solid metal structure
- Internal windscreen sponge
- Freq. Response: 50Hz to 15kHz
- Impedance: 700? +/- 30%
- Sensitivity: -54+/-3dB
- Includes: 20' cable (XLR plug for MCHH100 and 1/4" phono plug for MCHH100P)
- Microphone stand adapter



**MCHH100**

## Professional Condenser Microphone

- Back Electret Condenser
- Uni-directional
- Zinc-die Casting Housing
- Ideal for Clear Reproduction of Natural Sound
- 50Hz-18kHz
- 600-Ohms impedance
- Sensitivity:-45dB±3dB
- Max. Input SPL: 130dB (at 1kHz ≥1% T.H.D)
- S/N Ratio: ≥70dB
- Phantom Power Requirement: 9V-52V DC phantom or 1.5V Battery



**MCHH300**

## Adjustable Gooseneck Tabletop Microphone

- Momentary switch for priority paging, & lock down switch for continuous use
- 6" gooseneck extension and 5' cord
- Cannon 3 pin XLR male connector
- Impedance: low-600 Ohms high-50 kHz
- Sensitivity: High-53dB +/- 3dB Low 71 dB +/- 3 dB



**MHL5S**

## Professional Boundary Microphone

- Back Electret Condenser
- Uni-directional
- Stealth Design
- 20ft. XLR Cable Included
- 60Hz-16kHz
- 250-Ohms impedance
- Sensitivity: -36dB±3dB
- 9V-52V DC Phantom Power Required
- Mute Feature



**MCBM300**

## Professional Tabletop Conference Microphone

- Back Electret Condenser
- Uni-directional
- Flexible Gooseneck
- Easy Touch On/Off Button
- Blue LED On/Off Indicator
- 50Hz-16kHz • 500-Ohms impedance
- Sensitivity: -37dB±3dB
- XLR 3 Pin Male Connector
- Two AA Batteries Included
- 20 ft. XLR Cable Included
- 9V-52V DC Phantom or 1.5V Battery
- Windscreen Sponge over Mic.



**MCDT300**

## Professional Hanging Microphone

- Back Electret Condenser
- Uni-directional
- Spring Neck Included
- 50Hz-16kHz
- 250-Ohms impedance
- Sensitivity: -37dB±3dB
- XLR 3 Pin Male Connector
- 9V-52V DC Phantom Power Required
- 20ft. cable included



**MCHM300**

## Push-To-Talk Handheld Microphone

- 5 wire
- For CB & professional communications
- 500-Ohms impedance
- Push-to-talk
- Unbalanced (TS) plug



1/4" phono plug **DM520**  
**DM520P**

## Dynamic Gooseneck Microphone with Push-To-Talk Switch

- Uni-directional
- 16 1/4" gooseneck
- 500-Ohms low impedance
- Mounting base



**MGS1**

## 48V DC Phantom Power Supply For Condenser Microphones

- Male XLR mic output connector
- Female XLR mic input connector
- 110/0V 60/50Hz • 5ft. AC power cord included



**MCPP100**