


Communication & Control Cables

WEST PENN WIRE

Communication & Control Cable Four Conductor / Unshielded



Description:

- ASTM Bare Copper • PVC insulation • Cabled construction • Overall PVC jacket

Rating:

- NEC Type CMR or CL2R
- (UL)-C(UL) Listed or (ETL)us - c(ETL)us Listed
- Meets 300V requirements as specified in the NEC
- Flame Rating: UL1666

Applications:

Indoor for:

- Intercom Systems
- Security Systems
- Sound and Audio
- Background Music
- Power-limited Control Circuits

Standard spool size 1000ft.

Catalog No.	No. of Cond.	Conductor Type & Nom. D.C.R	Insulation Type & Thickness Inches	Shielding	Jacket Type & Thickness Inches	Nom. O.D. Inches	NEC Type	Nom. Capacitance	Jacket Color
240	4	22 AWG Solid 17.5 Ω/Mft	PVC .010	None	PVC .015	.142	CMR	--	Gray
241	4	22 AWG (7x30) 17 Ω/Mft	PVC .010	None	PVC .015	.153	CMR	--	Gray
242	4	20 AWG (7x28) 10.5 Ω/Mft	PVC .010	None	PVC .015	.173	CMR	--	Gray
244	4	18 AWG (7x26) 6.2 Ω/Mft	PVC .010	None	PVC .015	.191	CMR	--	Gray
245	4	16 AWG (19x29) 4.2 Ω/Mft	PVC .010	None	PVC .015	.222	CMR	--	Gray
246	4	14 AWG (19x27) 2.7 Ω/Mft	PVC .014	None	PVC .015	.292	CL2R*	--	Gray
248	4	12 AWG (19x25) 1.7 Ω/Mft	PVC .014	None	PVC .015	.338	CL2R*	--	Gray

Burglar Wire

Rating:

- NEC Type CM

S241	4	22 AWG (7x30) 17 Ω/Mft	Poly-propylene .008	None	PVC .015"	.129	CM	--	White, Gray
------	---	---------------------------	---------------------	------	-----------	------	----	----	-------------

Special Notes:

- Selected Plenum Versions see pages 30 & 31
- Selected Indoor/Outdoor Aquaseal Water Resistant® Versions see pages 40 & 43.
- Select cables are available in our Easybox®
- *- CL2R Meets 150V requirements for Low Voltage Circuits

Color Code	
All Cables	1. Black, 2. Red, 3. White, 4. Green JACKET: Gray
S241	1. Black, 2. Red, 3. White, 4. Green JACKET: White, Gray