


Communication & Control Plenum Cables

WEST PENN WIRE

Plenum Communication & Control Cable Two Conductor / Unshielded Plenecon II® Extra Flexible



Description:

- ASTM Bare Copper • Polymer alloy insulation • Short over-all twist lengths • Overall plenum PVC jacket

Rating:

- NEC Type CMP or CL2P
- (UL)-C(UL) Listed or (ETL)us - c(ETL)us Listed
- Meets 300V requirements as specified in the NEC
- Flame Rating: NFPA-262 Smoke & Flame Test

Standard spool size 1000ft.

Catalog No.	No. of Cond.	Conductor Type & Nom. D.C.R	Insulation Type & Thickness	Shielding	Jacket Type & Thickness	Nom. O.D. Inches	NEC Type	Nom. Capacitance	Jacket Color
			Inches		Inches				
25221B	2	22 AWG (7x30) 17 Ω/Mft	Polymer alloy .010	None	Plenum PVC .015	.110	CMP	--	GY, BL
25222B	2	20 AWG (7x28) 10.5 Ω/Mft	Polymer alloy .010	None	Plenum PVC .015	.125	CMP	--	Gray
25224B	2	18 AWG (7x26) 6.2 Ω/Mft	Polymer alloy .010	None	Plenum PVC .015	.138	CMP	--	GY, BK, BN, GN, WH, BL, YE
25225B	2	16 AWG (19x29) 4.2 Ω/Mft	Polymer alloy .010	None	Plenum PVC .015	.159	CMP	--	GY, BK, BN
25226B	2	14 AWG (19x27) 2.7 Ω/Mft	Polymer alloy .012	None	Plenum PVC .015	.190	CL2P	--	GY, BK, BN
25227B	2	12 AWG (19x25) 1.7 Ω/Mft	Polymer alloy .012	None	Plenum PVC .015	.221	CL2P	--	GY, BK, BN

Special Notes:

- Plenum Installation Precautions see Technical Reference Section Page 194
- Select cables are available in our Easybox®

Color Code	
All Cables	1. Black, 2. Red
	JACKET: GY-Gray, BK-Black, BN-Brown, WH-White, YE-Yellow, BL-Blue, GN-Green