


MI-TSP SERIES **CONTINUOUS FLOW TRAP SEAL PRIMER**

SERIES





MODEL NO.	DESCRIPTION	LIST PRICE	ADD FOR: Chrome Plated (-CP)	SHIP WEIGHT (Lbs.)	CARTON QTY.	WEIGHT (Lbs.)	REPAIR KIT (-RK)
MI-TSP-1	1/2" Sweat	\$ 150.00	\$ 49.00	1.0	20	20	\$ 49.00
MI-TSP-2	1/2" Threaded	\$ 150.00	\$ 49.00	1.0	20	20	\$ 49.00
MI-TSP-3	1/2" Threaded with union	\$ 232.00	\$ 49.00	1.0	20	20	\$ 49.00
	connections						

Part number for MI-TSP-1,2,3, repair kit is MI-TSP-RK. (SUFFIX-RK)

M-500 PRESSURE DROP ACTIVATED TRAP SEAL PRIMERS **SERIES**

MIFAB MR-500, MI-500 & M2-500 SERIES pressure drop activated brass trap seal primer, with inlet opening of 1/2" male N.P.T. and outlet opening of female 1/2" N.P.T. Complete with four view holes and removable filter screen. Requires no adjustments and no air precharge. MIFAB'S Series of pressure activated trap seal primers (MR-500, M1-500 and M2-500) can be connected to any cold water line, and will be automatically activated when a valve or faucet, that is on the line, is opened. A pressure drop of three p.s.i. will activate all of the trap seal primers. MIFAB's Series of trap seal primers can be disassembled in the field. Their unique design permits filter replacement without affecting the performance of the primer. The "O" ring seals are tested for reliability at a temperature range of -40 degrees to 450 degrees F. The M-500 Series of trap seal primers do not require adjustment. The operating range for all of MIFAB's Series of trap seal primers is 20 to 125 p.s.i. All three models are listed with I.A.P.M.O. and C.S.A. and are tested and certified to the A.S.S.E. Standard 1018 and are so marked. U.S. Patent # 6,152,164




MODEL NO.	A	В	PIPE Flats			REPLACEMENT Cartridge (-RC)		
MR-500	4 1/8"	1 1/4"	1 1/8"	6	P.O.A.	P.O.A.		
M1-500	4 1/8"	1 1/4"	1 1/8"	10	P.O.A.	P.O.A.		
M2-500	4 1/8"	1 1/4"	1 1/8"	3	P.O.A.	P.O.A.		

MODEL NO.	DESCRIPTION	LIST PRICE	SHIP WEIGHT (Lbs.)	CARTON QTY.	CARTON WEIGHT (Lbs.)
MR-500	Up to 6 drains	P.O.A.	.75	25	18.35
M1-500	Up to 10 drains	P.O.A.	.75	25	18.35
M2-500	Up to 3 drains	P.O.A.	.75	25	18.35

ML-DU TRAP SEAL PRIMER **SERIES DISTRIBUTION UNIT**

MIFAB's MI-DU trap seal primer distribution unit is engineered to receive a metered amount of water from a trap seal primer and distribute the water equally to either two, three or four floor drain traps. Choose from either 1/2" or 5/8" compression connections by indicating suffix (-500) for 1/2" or suffix (-625) for 5/8". The lid of the distribution unit has the numbers "2", "3" and "4" marked on it. The body of the distribution unit has a guide marker on the top of the body.

The numbers and the guide marker are positioned by removing the three screws in the lid of the unit and rotating the lid to match the appropriate numbers with the guide marker to provide priming for the desired number of drains. Do not over torque the three lid screws when securing the lid back to the body. It is not necessary to install MIFAB's distribution unit perfectly level. The unique design will distribute water uniformly when out of level up to 5 degrees. Model MI-DU is listed with I.A.P.M.Ó.



			LIST PRICE -500	LIST PRICE -625		CARTON	CARTON WEIGHT
M	MODEL NO. DESCRIPTION		(-½" compression)	(-5/8" compression)	(Lbs.)	QTY.	(Lbs.)
N	/II-DU	Trap Seal Primer Distribution	P.O.A.	P.O.A.	.75	6	4.50
		unit that serves two, three or					
		four floor drain traps.					

See Counterline Price Book CLPB-2009-USA for List Prices and discount structure of M-500 and MI-DU Series of products.

Design and dimensions are subject to modification. Prices do not include applicable taxes. Visit www.mifab.com for the most recent product information.