

Communication & Control Cables

Communication & Control Cable Cluster Speaker Cable/ Twisted Pair Unjacketed

WEST PENN WIRE

Applications:

Indoor for:

- Cluster Speaker Cable
- Power-Limited Circuit Applications
- Sound and Audio
- Background Music

Description:

- ASTM Bare Copper • PVC Insulation with Nylon • Short overall twist Construction • Unjacketed

Rating:

- NEC Type CL2
- (UL) or (ETL)us Listed
- Flame Rating: UL1685

Standard spool size 1000ft.

Catalog No.	No. of Pairs	Conductor Type & Nom. D.C.R	Insulation Type & Thickness Inches	Shielding	Jacket Type & Thickness	Nom. O.D. Inches	NEC Type	Nom. Capacitance	Jacket Color
C205	1	16 AWG (19x29) 4.2 Ω/Mft	PVC .015 Nylon .005	None	None	.194	CL2	--	Unjacketed
C206	1	14 AWG (41x30) 2.7 Ω/Mft	PVC .015 Nylon .005	None	None	.222	CL2	--	Unjacketed
C207	1	12 AWG (65x30) 1.7 Ω/Mft	PVC .015 Nylon .005	None	None	.260	CL2	--	Unjacketed

Color Code	
All Cables	1. Black, 2. White
	JACKET: Unjacketed

Special Notes:

- Select cables are available in our Easybox®