

Communication & Control Cables

Communication & Control Cable 18 AWG Multiple Pair/ Unshielded featuring the PERFECT PAIR®

Applications:

Indoor for:

- Intercom Systems
- Security Systems
- Sound and Audio
- Background Music
- Power-limited Control Circuits



Description:

- ASTM Bare Copper • PVC insulation • Short overall twist construction • Overall PVC jacket

Rating:

- NEC Type CMR
- (UL) C(UL) Listed or c(ETL)us Listed
- Meets 300V requirements as specified in the NEC
- Flame Rating: UL1666

Standard spool size 1000ft.

Catalog No.	No. of Pairs	Conductor Type & Nom. D.C.R	Insulation Type & Thickness Inches	Shielding	Jacket Type & Thickness Inches	Nom. O.D. Inches	NEC Type	Nom. Capacitance	Jacket Color
751	2	18 AWG (7x26) 6.2 Ω/Mft	PVC .010	None	PVC .015	.248	CMR	32 pf/ft*	Gray
752	3	18 AWG (7x26) 6.2 Ω/Mft	PVC .010	None	PVC .015	.275	CMR	32 pf/ft*	Gray
753	4	18 AWG (7x26) 6.2 Ω/Mft	PVC .010	None	PVC .020	.302	CMR	32 pf/ft*	Gray
754	6	18 AWG (7x26) 6.2 Ω/Mft	PVC .010	None	PVC .020	.366	CMR	32 pf/ft*	Gray
755	9	18 AWG (7x26) 6.2 Ω/Mft	PVC .010	None	PVC .020	.432	CMR	32 pf/ft*	Gray

* Capacitance between conductors.

Color Code	
Colors	Colors
1. Black/Red-Red	6. Black/Brown-Brown
2. Black/White-White	7. Black/Orange-Orange
3. Black/Green-Green	8. Red/White-White
4. Black/Blue-Blue	9. Red/Green-Green
5. Black/Yellow-Yellow	
JACKET: Gray	

Special Notes:

- Select cables are available in our Easybox®
- Orange ripcord included on cables containing 3 or more pairs
- Selected Plenum Versions see pages 31