


Communication & Control Plenum Cables

WEST PENN WIRE



Plenum Communication & Control Cable Multiple Conductor/ Unshielded 16, 18, and 20 AWG Plenecon II® Extra Flexible

Applications:

Indoor within ducts, plenums and other spaces used for environmental air:

- Intercom Systems
- Security Systems
- Sound and Audio
- Background Music

Description:

- ASTM Bare Copper • Polymer alloy insulation • Cabled construction • Overall plenum PVC jacket

Rating:

- NEC Type CMP
- (UL) -C(UL) Listed or c(ETL)us Listed
- Meets 300V requirements as specified in the NEC
- Flame Rating: NFPA-262 Smoke & Flame Test

Standard pool size 1000ft.

Catalog No.	No. of Cond.	Conductor Type & Nom. D.C.R	Insulation Type & Thickness	Shielding	Jacket Type & Thickness	Nom. O.D.	NEC Type	Nom. Capacitance	Jacket Color
			Inches		Inches				
25232B New	3	20 AWG (7x28) 10.5 Ω/Mft	Polymer alloy .010	None	Plenum PVC .015	.150	CMP	--	Gray
25242B	4	20 AWG (7x28) 10.5 Ω/Mft	Polymer alloy .010	None	Plenum PVC .015	.170	CMP	--	Gray
25234B	3	18 AWG (7x26) 6.2 Ω/Mft	Polymer alloy .010	None	Plenum PVC .015	.173	CMP	--	Gray
25244B	4	18 AWG (7x26) 6.2 Ω/Mft	Polymer alloy .010	None	Plenum PVC .015	.189	CMP	--	Gray
25186B	6	18 AWG (7x26) 6.2 Ω/Mft	Polymer alloy .010	None	Plenum PVC .015	.228	CMP	--	Gray
25188B New	8	18 AWG (7x26) 6.2 Ω/Mft	Polymer alloy .010	None	Plenum PVC .015	.241	CMP	--	Gray
25245B New	4	16 AWG (19x29) 4.2 Ω/Mft	Polymer alloy .010	None	Plenum PVC .015	.221	CMP	--	Gray

Special Notes:

- Plenum Installation Precautions see Technical Reference Section Page 194
- Select cables are available in our Easybox®

Color Code	
Colors	Colors
1. Black	5. Brown
2. Red	6. Blue
3. White	7. Orange
4. Green	8. Yellow
JACKET: Gray	