

# Communication & Control Cables

**WEST PENN WIRE**



## Communication & Control Cable Sound and Audio / Special Cable

### Description:

- ASTM Bare Copper • PVC insulation • Unshielded/ Shielded pair 100% coverage of aluminum polyester foil with drain wire • Short overall twist construction • Overall PVC jacket

### Rating:

- NEC Type CMR
- (UL)-C(UL) Listed or c(ETL)us Listed
- Meets 300V requirements as specified in the NEC
- Flame Rating: UL1666

### Applications:

#### Indoor for:

- Intercom Systems
- Security Systems
- Sound and Audio
- Background Music
- Power-limited Control Circuits

Standard pool size 1000ft.

Catalog No.	No. of Cond.	Conductor Type & Nom. D.C.R	Insulation Type & Thickness	Shielding & % Coverage	Jacket Type & Thickness	Nom. O.D.	NEC Type	Nom. Capacitance	Jacket Color
			Inches	% Coverage	Inches				
351	3 (2 Shld) (1 Unshld)	22 AWG Solid 17.5 Ω/Mft	PVC .010	Al. Foil 100% 22 Solid	PVC .015	.159	CMR	54 pf/ft* 97 pf/ft**	Gray
352	3 (2 Shld) (1 Unshld)	22 AWG (7x30) 17 Ω/Mft	PVC .010	Al. Foil 100% 24 Strd.	PVC .015	.169	CMR	55 pf/ft* 99 pf/ft**	Gray
355	4 (2 Shld) (2 Unshld)	22 AWG Solid 17.5 Ω/Mft	PVC .010	Al. Foil 100% 22 Solid	PVC .015	.156	CMR	54 pf/ft* 97 pf/ft**	Gray
356†	4 (2 Shld) (2 Unshld)	20 (7x28) 18 (7x26)	PVC .010	Al. Foil 100% drain	PVC .015	.200	CMR	60 pf/ft* 108 pf/ft**	Gray
357	4 (2 Shld) (2 Unshld)	22 AWG (7x30) 17 Ω/Mft	PVC .010	Al. Foil 100% 24 Strd.	PVC .015	.168	CMR	55 pf/ft* 99 pf/ft**	GY, BL
358	3 (2 Shld) (1 Unshld)	20 AWG (7x28) 10.1 Ω/Mft	PVC .010	Al. Foil 100% 22 Strd.	PVC .015	.189	CMR	60 pf/ft* 108 pf/ft**	Gray
359	4 (2 Shld) (2 Unshld)	20 AWG (7x28) 10.1 Ω/Mft	PVC .010	Al. Foil 100% 22 Strd.	PVC .015	.191	CMR	60 pf/ft* 108 pf/ft**	Gray
360	4 (2 Shld) (2 Unshld)	18 AWG (7x26) 6.2 Ω/Mft	PVC .010	Al. Foil 100% 22 Strd.	PVC .015	.209	CMR	68 pf/ft* 122 pf/ft**	Gray
369	6 (2 Shld) (4 Unshld)	22 AWG Solid 17.5 Ω/Mft	PVC .010	Al. Foil 100% 22 Solid	PVC .015	.174	CMR	54 pf/ft* 97 pf/ft**	Gray

### Special Notes:

- Selected Plenum Versions see pages 35
- Selected Indoor/Outdoor Aquaseal Water Resistant® Versions see pages 38
- Select cables are available in our Easybox®
- Orange ripcord included on cables containing 5 or more conductors
- † Shielded pair contains 22AWG strd.drain wire

\* Capacitance between conductors.

\*\* Capacitance between one conductor and the other connected to the shield

### Color Code

Catalog Number	351, 352, 355, 356, 357, 358, 359, 360	369
Primary Color Code	Shielded: Black, Red Unshielded: White, Green	1. Black, 2. Red, 3. White, 4. Green, 5. Brown, 6. Blue

**JACKET:** GY-Gray, BL-Blue