

Quality DMMs at an Affordable Price

For general Electrical, Electronic, Security, Integration, HVAC, Troubleshooting & Repair needs. The 9005-A and 9015-A have an Ergonomically Shaped Case and a HUGE Digital Display!



Model 9005-A

Digital Multimeter

- ▲ 3 1/2 Digit, 1999 max. reading
- ▲ HUGE, 1.15" High Digital Display
- ▲ Manual Range Selection
- ▲ DC Voltage to 1000V
- ▲ AC Voltage to 750V
- ▲ AC/DC Current to 10A
- lacktriangle Resistance to 200M Ω
- ▲ Continuity Test
- Diode Check
- ▲ Transistor Check
- ▲ Data Hold
- Auto Polarity
- ▲ Low Battery Indication
- Auto Power Off
- Double Insulated Case
- Safety designed to comply with IEC 1010-1
- ▲ CAT I, II, and III Rated
- Overload Protected
- ▲ Three Year Warranty
- ▲ Includes: Red Rubber Boot, Safety Test Leads with Screw-On Alligator Clips & 9 Volt Battery

Cat. No. 9005: Model 9005-A



Model 9015-A

Digital Multimeter with Temperature & Capacitance

- ▲ 3 1/2 Digit, 1999 max. reading
- ▲ HUGE 1.15" High Digital Display
- ▲ Manual Range Selection
- ▲ DC Voltage to 1000V
- ▲ AC Voltage to 750V
- ▲ AC/DC Current to 10A
- lacktriangle Resistance to 200M Ω
- ▲ Temperature Test (Probe Included)
- Capacitance Test (Extension Lead Included)
- Frequency
- ▲ Continuity Test
- ▲ Diode Check
- ▲ Transistor Check
- Data Hold
- Auto Polarity
- ▲ Low Battery Indication
- Auto Power Off
- ▲ Double Insulated Case
- ▲ Safety designed to comply with IEC 1010-1
- ▲ CAT I, II, and III Rated
- Overload Protected
- ▲ Three Year Warranty
- ▲ Includes: Red Rubber Boot, Safety Test Leads with Screw-On Alligator Clips, Thermocouple Probe, Capacitance Extension Lead & 9 Volt Battery

Cat. No. 9015: Model 9015-A



Model 9045.

True RMS Digital Multimeter with Temperature, Capacitance & Frequency

- ▲ 6000 Count Display
- ▲ 61 Segment Bargraph
- ▲ Blue Backlit LCD
- Auto / Manual Ranging
- ▲ DC Voltage Ranges to 1000V
- ▲ AC Voltage Ranges to 750V
- ▲ AC/DC Current Ranges to 10A
- \blacktriangle Resistance Ranges from 600Ω to $60M\Omega$
- ▲ Temperature Test (° F & ° C Selectable)
- ▲ Capacitance Ranges from 40nF to 4000μF
- ▲ Frequency Ranges from 9.999Hz to 9.999MHz
- ▲ Duty Cycle
- ▲ Diode Test
- ▲ Continuity Test
- Auto Polarity
- ▲ Relative Mode
- ▲ Data Hold
- ▲ Range Hold
- ▲ Min/Max
- ▲ Flexible Auto Power Off
- ▲ Splash Proof / Dust Proof Case
- ▲ Ergonomic, Overmolded, Shock Absorbing Case w/ Stand
- ▲ Safety designed to comply with IEC 1010-1
- ▲ CAT III 600 Volt / CAT II 1000 Volt Rated
- Overload Protected
- ▲ Three Year Warranty
- ▲ Includes: Safety Test Leads with Screw-On Alligator Clips, Thermocouple Probe & 9 Volt Battery

Cat. No. 9045: Model 9045



9045

The Sleek, New 9045 has a Ergonomic, Overmolded, Shock Absorbing Case with Test Lead holders. This HOT New DMM is LOADED with Features and Functions at an Affordable Price!

TRIPLETT



