

PERFECT SOUND FROM EAR TO EAR.



SRH240

Professional Quality Headphones



High Quality Sound and Comfort

Reproducing full bass with detailed highs, the SRH240 is ideal for vivid listening on almost any device. The closed-back, circumaural design rests comfortably over the ears and reduces background noise.



Accessories Included



THREADED 1/4"
NICKEL-PLATED
ADAPTER

SRH440

Professional Studio Headphones



Accurate Monitoring for Recording and Playback

Tuned to deliver accurate audio reproduction and featuring an adjustable headband with collapsible construction, the SRH440 offers a mix of professional sound quality and comfort ideal for recording and monitoring.



Accessories Included



DETACHABLE
COILED CABLE



THREADED 1/4"
GOLD-PLATED
ADAPTER



CARRYING BAG

SRH750DJ

Professional DJ Headphones



Sound, Style and Flexibility

The SRH750DJ features 50 mm neodymium dynamic drivers tuned to deliver high-output bass with extended highs. Ear cups that swivel 90° make the SRH750DJ perfect for meeting the demands of live professional DJ mixing and monitoring.



Accessories Included



ADDITIONAL PAIR
OF EAR PADS



DETACHABLE
COILED CABLE



THREADED ¼"
GOLD-PLATED
ADAPTER



CARRYING BAG

SRH840

Professional Monitoring Headphones



Precision Performance for Critical Listening

Featuring 40 mm neodymium dynamic drivers precisely tailored to deliver rich bass, clear mid-range and extended highs needed for critical listening and studio monitoring. The SRH840 also provides an ergonomic fit and collapsible design for comfort and portability.



Accessories Included



ADDITIONAL PAIR
OF EAR PADS



DETACHABLE
COILED CABLE



THREADED ¼"
GOLD-PLATED
ADAPTER



CARRYING BAG

LEGENDARY SHURE QUALITY

Designed to withstand the rigors of everyday use, Shure headphones are engineered to the same precise standards that have made Shure a leader in professional audio for over 80 years.



SRH240

Professional Quality Headphones



SRH440

Professional Studio Headphones



SRH750DJ

Professional DJ Headphones



SRH840

Professional Monitoring Headphones

FEATURES

Wide frequency range delivers full bass and detailed highs

Optimized performance for use with most pro and consumer audio devices

Legendary Shure quality to withstand the rigors of everyday use

Enhanced frequency response delivers accurate audio across an extended range

Impedance and power handling optimized for performance with professional audio devices

Adjustable headband and collapsible construction provide comfort and portability

Bayonet clip securely locks detachable cable into ear cup

Enhanced frequency response tuned to deliver high-output bass with extended highs

High impedance and maximized power handling for DJ mixers

Adjustable, collapsible headband with 90-degree swivel ear cups for comfort and easy one-ear placement

Replacement set of ear cup pads included to ensure long product life

Bayonet clip securely locks detachable cable into ear cup

Precisely tailored frequency response delivers rich bass, clear mid-range and extended highs

Closed-back, circumaural design rests comfortably over the ears and reduces background noise

Wide, padded headband provides ergonomic fit for superior comfort over extended periods

Replacement set of ear cup pads included to ensure long product life

Bayonet clip securely locks detachable cable into ear cup

SPECIFICATIONS

Transducer type:

Dynamic neodymium magnet

Driver size: 40 mm

Sensitivity (1kHz): 107 dB/mW

Impedance (1kHz): 38 Ω

Max. input power (1kHz): 500 mW

Frequency range: 20 Hz – 20 kHz

Net weight (without cable):

.4 lb (181 g)

Shipping weight: 1.35 lbs (612 g)

Length of cable: 2 meters (6.56 ft)

Type of cable: Attached straight oxygen-free copper

Plug: Gold-plated 1/8" (3.5 mm) stereo mini jack

Transducer type:

Dynamic neodymium magnet

Driver size: 40 mm

Sensitivity (1kHz): 105 dB/mW

Impedance (1kHz): 44 Ω

Max. input power (1kHz): 500 mW

Frequency range: 10 Hz – 22 kHz

Net weight (without cable):

.6 lb (272 g)

Shipping weight: 1.55 lbs (703 g)

Length of cable: 3 meters (9.84 ft)

Type of cable: Detachable coiled oxygen-free copper

Plug: Gold-plated 1/8" (3.5 mm) stereo mini jack

Transducer type:

Dynamic neodymium magnet

Driver size: 50 mm

Sensitivity (1kHz): 106 dB/mW

Impedance (1kHz): 32 Ω

Max. input power (1kHz): 3000 mW

Frequency range: 5 Hz – 30 kHz

Net weight (without cable):

.5 lb (227 g)

Shipping weight: 1.55 lbs (703 g)

Length of cable: 3 meters (9.84 ft)

Type of cable: Detachable coiled oxygen-free copper

Plug: Gold-plated 1/8" (3.5 mm) stereo mini jack

Transducer type:

Dynamic neodymium magnet

Driver size: 40 mm

Sensitivity (1kHz): 102 dB/mW

Impedance (1kHz): 44 Ω

Max. input power (1kHz): 1000 mW

Frequency range: 5 Hz – 25 kHz

Net weight (without cable):

.7 lb (317.5 g)

Shipping weight: 1.75 lbs (794 g)

Length of cable: 3 meters (9.84 ft)

Type of cable: Detachable coiled oxygen-free copper

Plug: Gold-plated 1/8" (3.5 mm) stereo mini jack

SHURE[®]
LEGENDARY
PERFORMANCE™

**United States, Canada,
Latin America, Caribbean:**
Shure Incorporated
5800 West Touhy Avenue
Niles, IL 60714-4608 USA

Phone: 847-600-2000
Fax: 847-600-1212 (USA)
Fax: 847-600-6446
Email: info@shure.com

Europe, Middle East, Africa:
Shure Europe GmbH
Wannenäckerstr. 28,
74078 Heilbronn, Germany

Phone: 49-7131-72140
Fax: 49-7131-721414
Email: info@shure.de

Asia, Pacific:
Shure Asia Limited
22/F, 625 King's Road
North Point, Island East,
Hong Kong

Phone: 852-2893-4290
Fax: 852-2893-4055
Email: info@shure.com.hk