

**Products**
[Home](#) > [Products](#) > [Integrated Systems](#) > [Classrooms & Boardrooms](#) >

- New Products
- Designer Solutions
- MultiTasker
- Twisted Pair
- Matrix Switchers
- Dedicated AV
- AV Control System
- Cables
- Integrated Systems
- Audio Solutions
- Accessories
- Application Diagrams
- Downloads
- Applications
- Retired Products

## YZ810-106

### VGA + Stereo Wall Plate (w/Local Monitor Loop Thru)

- Converts RGBHV + Stereo to UTP (CAT 5)
- Local Buffered RGBHV (VGA) Output
- Powered by Showtime Integrated Switcher
- Up to UXGA at 50'

Want to tell us what you think?  
 Feel free to post your comments here:  
 (Please include your email address if you  
 would like us to respond.)


[Printable Version](#)


ISO 9001:2000  
 Certified

The **YZ810-106** VGA-UXGA wall panel allows the video and audio from a computer to be presented through the Showtime system. An output VGA connector provides a local monitor output. The audio input uses a 3.5 mm jack and the video input is a standard 15-pin HD female connector. The signals are combined and output over two standard CAT 5 cables attached to the rear of the unit inside the wall. External power is not required since the unit receives power from the Showtime switcher. There is a Power/Signal Present LED on the front of the panel. The LED is on and red if the unit has power. The LED changes from red to green when a valid computer video signal is present.

### Specifications

GENERAL	ELECTRICAL
<b>Inputs</b>	<b>Inputs</b>
Video: (1) 15pin HD female	Analog Video Signal: 1.2V p-p max
Audio: (1) 3.5mm female	Video Impedance: 75ohms
<b>Outputs</b>	SYNC Signal: TTL (+/-)
Video: (1) 15pin HD female	SYNC Impedance: 10kohms
Video + Audio: (2) RJ-45 female	Audio Signal: 1.0V p-p max
<b>Compatibility</b>	<b>Outputs</b>
Signal Types (Computer): RGBHV	Video + Audio + Power: ALTINEX standard for Showtime systems
Video Resolutions: VGA ~ UXGA	<b>Power Consumption:</b>
	+7.5VDC max, 0.2A (1.5W)
<b>MECHANICAL</b>	
Material: Steel	
Finish: White	
<b>Body</b>	
Height: 2.6in (66mm)	
Width: 1.4in (36mm)	
Length(excluding cables): 1.2in (30mm)	
Length(inside electrical box): 1.0in (25mm)	
<b>Body with Mounting Tabs</b>	
Height: 4.1in (104mm)	
Width: 1.4in (36mm)	
Length(excluding cables): 1.2in (30mm)	
Weight: 0.2lbs (0.1kg)	
Ship Weight: 0.5lbs (0.2kg)	
T° Operating: 10°C-35°C	
T° Maximum: 50°C	

Humidity: 90° non-condensing

---

Specifications/Diagrams subject to change without notice.

Copyright © 2010 ALTINEX, Inc. All rights reserved. | v5.0 | **1.800.ALTINEX** | [Terms of Use](#) | [Terms & Conditions](#) | [Privacy](#)