

Communication & Control Cables

WEST PENN WIRE



Communication & Control Cable 22 AWG Multiple Conductor / Overall Shielded featuring the **PERFECT STRIPE**®

Description:

- ASTM Bare Copper • PVC insulation • Overall shield 100% coverage of aluminum polyester foil with 24 AWG Strd. TC drain wire • Cabled construction • Overall PVC jacket

Rating:

- NEC Type CMR
- (UL)-C(UL) Listed or c(ETL)us Listed
- Meets 300V requirements as specified in the NEC
- Flame Rating: UL1666

Applications:

Indoor for:

- Intercom Systems
- Security Systems
- Sound and Audio
- Background Music
- Power-limited Control Circuits

Standard spool size 1000ft.

Catalog No.	No. of Cond.	Conductor Type & Nom. D.C.R	Insulation Type & Thickness	Shielding & % Coverage	Jacket Type & Thickness	Nom. O.D. Inches	NEC Type	Nom. Capacitance	Jacket Color
			Inches		Inches				
3241	4	22 AWG (7x30) 17 Ω/Mft	PVC .010	Al. Foil 100%	PVC .015	.157	CMR	55 pf/ft* 99 pf/ft**	Gray
3855	5	22 AWG (7x30) 17 Ω/Mft	PVC .010	Al. Foil 100%	PVC .015	.172	CMR	55 pf/ft* 99 pf/ft**	Gray
3270	6	22 AWG (7x30) 17 Ω/Mft	PVC .010	Al. Foil 100%	PVC .015	.187	CMR	55 pf/ft* 99 pf/ft**	Gray
3271	8	22 AWG (7x30) 17 Ω/Mft	PVC .010	Al. Foil 100%	PVC .015	.212	CMR	55 pf/ft* 99 pf/ft**	Gray
3272	10	22 AWG (7x30) 17 Ω/Mft	PVC .010	Al. Foil 100%	PVC .015	.247	CMR	55 pf/ft* 99 pf/ft**	Gray
3273	12	22 AWG (7x30) 17 Ω/Mft	PVC .010	Al. Foil 100%	PVC .015	.255	CMR	55 pf/ft* 99 pf/ft**	Gray
3274	15	22 AWG (7x30) 17 Ω/Mft	PVC .010	Al. Foil 100%	PVC .020	.282	CMR	55 pf/ft* 99 pf/ft**	Gray
3275	20	22 AWG (7x30) 17 Ω/Mft	PVC .010	Al. Foil 100%	PVC .020	.312	CMR	55 pf/ft* 99 pf/ft**	Gray

Color Code- See pg. 9

* Capacitance between conductors.

** Capacitance between one conductor and the other connected to the shield

Special Notes:

- Selected Plenum Versions see pages 33
- Select cables are available in our Easybox®
- Orange ripcord included on cables containing 5 or more conductors