
Drum Faucets For Hazardous Liquids



Dispensing faucets for horizontal drums.

Justrite's Self-closing Drum Safety Faucets incorporate an internal flame arrester which prevents flashback of fire into the drum. All faucets are gasketed to prevent leakage. Most faucets for ¾" NPT bung have threading in the spout to accommodate a hose extension. Faucet hose extensions provide extra dispensing accuracy and prevents spills. Adjustable faucets screw tightly into drum and can be adjusted to dispensing position, with spout downward, without thread damage or leakage.

For trouble-free dispensing of viscous, noncorrosive flammables such as adhesives, paint or heavy oils above 2000 SSU (about 30W oil), use Justrite's **2" Gate Valves** and/or **%" Viscous Liquids Faucets.** Flame arresters are not provided on viscous liquid faucets.



Drum Faucets Description	External Bung Thread NPT	Wetted O-Rings	Internal Spout Thread	Approv./Lstg. Regulation*	Model No.
Brass Safety Faucet, Rigid	3/4"	PTFE	¹³ /16 - 27 UNS 2B	FM	08902
Brass Safety Faucet, Adjustable	3/4"	PTFE	¹³ /16 - 27 UNS 2B	FM	08910
Zinc Safety Faucet, Rigid	3/4"	Buna-N	-	FM	08912
Zinc Safety Faucet, Adjustable	3/4"	Buna-N	¹³ /16 - 27 UNS 2B	FM	08913
Stainless Steel Safety Faucet, Adjustable	e ¾"	PTFE	¹³ /16 - 27 UNS 2B	FM	08916
Brass Control Flow Lab Safety Faucet	3/4"	PTFE	½ - 20 UNF	FM	08540
Brass Faucet, Viscous Liquids	3/4"	PTFE	-	FM	08955
Brass Drum Gate Valve, Viscous Liquids	s 2"	PTFE	-	FM	08552
Flexible Faucet Extension, 31/4" long, Brass for use with Nos. 08902, 08910			10 –	-	08932
Flexible Faucet Extension, 6" long, Stainless Steel for use with No. 08916			-	-	08587
Flexible Faucet Extension, 6" long, Brass for use with No. 08540			-	-	08584
Flexible Faucet Extension, 8" long, Bras	_	-	08930		

Note: PTFE is a synthetic fluoropolymer.



Maximum draining of a horizontally stored drum.

Justrite's Drum Siphon Adapter is the simple solution for nearly complete drainage of liquids out of 30- and 55-gallon (110 & 200L) drums, eliminating the need for dangerous drum tipping or rolling. Unique siphon action empties residual solvents from a typical two to three gallons down to the last few ounces. Made of solid cast brass, the adapter will hold-up under heavy use with compatible liquids. One end of the adapter accepts a standard ¾" drum faucet and the opposite end screws into a ¾" drum bung opening. An adjustable collar accommodates bungs in varying positions to maximize siphoned liquid volume. Not only are you getting the benefit of using nearly all the drum contents, you won't have to pay the high cost associated with removal of large volumes of hazardous liquids.

Drum Siphon Adapter

Description	Model No.
Brass Drum Siphon Adapter	08311
Brass Adapter No. 08311 & Brass Self-closing Faucet No. 08	902 08308

*See page 8 for Regulation Key.

