

Specialty Cabinets **FOR FLAMMABLES**

Aerosol Can Benchtop Sure-Grip® EX Safety Cabinet fits up to twenty-four aerosol cans in two easy roll-out shelves!

Justrite's Aerosol Can Benchtop Safety Cabinet fits virtually anywhere for hassle-free organization of aerosol cans. Constructed of sturdy, double-wall, 18-gauge (1mm) welded steel, it has 1½" (38mm) of insulating air space for fire resistance. Now with Haz-Alert™ warning label. Cabinet features 24-gauge galvanized steel roll-out shelves with "easy-glide" plastic rollers and stop guard protection. Two fixed position shelves have twelve 2¾" (70mm) diameter openings, accepting cans up to 10" (254mm) tall, and are removable for easy cleaning. U•Loc™ flush-mounted padlockable handle with gripper pad allows easy fingertip controlled opening. Locking mechanism with double key set secures contents. Cabinet is finished inside-and-out with a durable, lead-free, hybrid epoxy/polyester powder paint for chemical resistance. Backed by Justrite's Ten-Year Warranty. Meets NFPA Code 30 and OSHA regulations. Ships fully assembled. For storage of larger quantities of aerosol cans see page 22.



Durable, 24-gauge steel shelves slide smoothly with "easy-glide" plastic rollers. "Stop guard" protection assures shelves won't fall out when fully extended.

Aerosol Can Benchtop Safety Cabinet

Capacity	Dimensions H x W x D (mm)	Roll-out Drawers	Approv./Lstg. Regulation*	Ship Wt. Lbs./Kgs.	Model No.
24 cans	27" x 21" x 18" (686 x 533 x 457)	2	N,O	97/44	890500

– For Canada –

Double-wall Cabinets with 2" (51mm) of high-density insulation withstand the most stringent fire testing.

When only the best will do, look to Justrite's ULC listed cabinets which comply with OSHA and NFPA as well as the strict testing requirements of the National Fire Code of Canada. With a full 2" (51mm) of high density insulation within the walls, doors, ceiling and floors and intumescent tape (which expands to eight times its volume to seal the doors) these cabinets assure the utmost in protection. Other premium features include a superior powder coat paint finish over rugged, unitized, 18-gauge (1mm) welded steel, a 2" (51mm) leakproof spill containment sill, adjustable shelves, vent openings with flame arresters, leveling feet and a three-point lock for security.



NX25450



Premium Insulated Cabinets, ULC Listed

Number of Doors and Style	Capacity Gallons	Ext. Dimensions H x W x D (mm)	Adjustable Shelves	Approv./Lstg. Regulation*	Ship Wt. Lbs./Kgs.	Model No.
2 door, manual	30/114L	44" x 43" x 18" (1118 x 1092 x 457)	1	FM,ULC,N,O	310/141	NX25300
2 door, manual	45/170L	65" x 43" x 18" (1651 x 1092 x 457)	2	FM,ULC,N,O	431/196	NX25450

*See page 8 for Regulation Key.



1-800-798-9250 • Fax: 1-800-488-5877 • www.justritemfg.com