

REGAL-BELOIT SpinMaster™ Plus AC Adjustable Speed Drives

Volts/Hertz Constant Torque, Micro Inverter



REGAL-BELOIT
SpinMaster® plus

Applications: Constant torque or constant horsepower applications. Typical applications include conveyors, packaging machinery, machine tool, printing equipment, and specialty equipment.

- Features:**
- Current limit to 180% with frequency foldback
 - Adjustable carrier frequency
 - Independent accel and decel adjustment
 - RS-485 Communications
 - Adjustable DC injection braking
 - Programmable inputs
 - MODBUS protocol
 - Fixed boost for high starting torque
 - UL Listed and UL Certified for Canada under File No. E197830
 - IP20 enclosure
 - Unlimited lead length with microMAX™, Black Max® or Blue Max®, AC motor
 - 2 year warranty

Single or Three Phase Input / Three Phase Output

HP / kW	INPUT PHASE	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	STOCK MODEL	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
										IN / MM	IN / MM	IN / MM	
.25 / .20	1	208/240	3.6/3.2	1.6/1.4	T310		\$507	D3	1.9	5.75/146	3.66/93	3.94/100	
	3		1.9/1.7										
.5 / .37	1	208/240	5.4/4.7	2.5/2.2	T312	*	\$529	D3	1.9	5.75/146	3.66/93	3.94/100	
	3		3.1/2.7										
1 / .75	1	208/240	10.6/9.2	4.8/4.2	T314	*	\$570	D3	2.5	5.75/146	3.66/93	4.74/120	
	3		5.8/5.1										
1.5 / 1.1	1	208/240	13.9/12.0	6.9/6.0	T315		\$677	D3	3.5	5.75/146	4.52/115	5.24/133	
	3		8.0/6.9										
2 / 1.5	1	208/240	14.8/12.9	7.8/6.8	T316		\$749	D3	4.5	5.75/146	4.52/115	6.74/171	
	3		9.1/7.9										
3 / 2.2	1	208/240	19.7/17.1	11.0/9.6	T317	*	\$910	D3	4.8	5.75/146	4.52/115	6.74/161	FN
	3		12.4/10.8										
5 / 3.7	1	208/240	29/26	17.5/15.2	T318	*	\$1,247	D3	7.6	7.75/197	5.78/147	7.18/182	FN
	3		19.6/17.1										

Three Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	STOCK MODEL	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
									IN / MM	IN / MM	IN / MM	
1 / .75	208/240	5.8/5.1	4.8/4.2	T324	*	\$525	D3	2.5	5.75/146	3.66/93	4.74/120	
1.5 / 1.1	208/240	8.0/6.9	6.9/6.0	T325		\$618	D3	3	5.75/146	3.66/93	5.74/146	
2 / 1.5	208/240	9.1/7.9	7.8/6.8	T326	*	\$681	D3	3.1	5.75/146	3.66/93	5.74/146	FN
3 / 2.2	208/240	12.4/10.8	11.0/9.6	T327	*	\$812	D3	3.2	5.75/146	3.66/93	5.74/146	FN
5 / 3.7	208/240	19.6/17.1	17.5/15.2	T328		\$1,045	D3	4.6	5.75/146	4.52/115	6.74/171	FN
7.5 / 5.5	208/240	28.0/25.0	25.0/22.0	T329	*	\$1,427	D3	7.3	7.75/197	5.78/147	7.18/182	FN
10 / 7.5	208/240	34.0/32.0	30.0/28.0	T330		\$1,705	D3	7.5	7.75/197	5.78/147	7.18/182	FN
15 / 11	208/240	54.0/48.0	48.0/42.0	T331	*	\$2,209	D3	13	9.75/248	7.68/195	8.00/203	FN
20 / 15	208/240	65.0/61.0	58.0/54.0	T333	*	\$2,710	D3	13.5	9.75/248	7.68/195	8.00/203	d, FN

Continued on next page.

REGAL-BELOIT SpinMaster™ Plus AC Adjustable Speed Drives

Volts/Hertz Constant Torque, Micro Inverter

Three Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	STOCK MODEL	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
									IN / MM	IN / MM	IN / MM	
.5 / .37	480	1.4	1.1	T332	*	\$591	D3	1.9	5.75/146	3.66/93	3.94/100	
1 / .75	480	2.5	2.1	T334	*	\$637	D3	2.4	5.75/146	3.66/93	4.74/120	
1.5 / 1.1	480	3.6	3.0	T335	*	\$696	D3	2.9	5.75/146	3.66/93	5.74/146	
2 / 1.5	480	4.0	3.4	T336	*	\$768	D3	3.1	5.75/146	3.66/93	5.74/146	
3 / 2.2	480	5.4	4.8	T337	*	\$858	D3	3.2	5.75/146	3.66/93	5.74/146	FN
5 / 3.7	480	8.6	7.6	T338	*	\$1,094	D3	4.6	5.75/146	4.52/115	6.74/171	FN
7.5 / 5.5	480	12.4	11.0	T339	*	\$1,427	D3	7.2	7.75/197	5.78/147	7.18/182	FN
10 / 7.5	480	15.8	14.0	T340	*	\$1,705	D3	7.5	7.75/197	5.78/147	7.18/182	FN
15 / 11	480	24.0	21.0	T341	*	\$2,166	D3	13.3	9.75/248	7.68/195	8.00/203	FN
20 / 15	480	31.0	27.0	T342	*	\$2,652	D3	13.5	9.75/248	7.68/195	8.00/203	FN
25 / 18.5	480	38.0	34.0	T343	*	\$3,156	D3	13.8	9.75/248	7.68/195	8.00/203	FN
30 / 22.4	480	45.0	40.0	T344	*	\$3,669	D3	14.5	9.75/248	7.68/195	8.00/203	FN
1 / .75	575	2.0	1.7	T354	*	\$681	D3	2.4	5.75/146	3.66/93	4.74/120	
2 / 1.5	575	3.5	3.0	T356	*	\$816	D3	3.1	5.75/146	3.66/93	5.74/146	
3 / 2.2	575	4.7	4.2	T357	*	\$969	D3	4.1	5.75/146	4.52/115	6.74/171	FN
5 / 3.7	575	7.4	6.6	T358	*	\$1,185	D3	4.7	5.75/146	4.52/115	6.74/171	FN
7.5 / 5.5	575	11.2	9.9	T359	*	\$1,539	D3	7.1	7.75/197	5.78/147	7.18/182	FN
10 / 7.5	575	13.7	12.2	T360	*	\$1,824	D3	7.4	7.75/197	5.78/147	7.18/182	FN
15 / 11	575	22.0	19.0	T361	*	\$2,389	D3	13.3	9.75/248	7.68/195	8.00/203	FN
20 / 15	575	27.0	24.0	T362	*	\$2,922	D3	13.5	9.75/248	7.68/195	8.00/203	FN
25 / 18.5	575	31.0	27.0	T363	*	\$3,456	D3	13.8	9.75/248	7.68/195	8.00/203	FN

AC DRIVES

SpinMaster Plus Drive Options

Add the suffix Letter to the SpinMaster™ Plus Catalog #.
(Available on the SpinMaster™ Plus series as a build-up ONLY)

DESCRIPTION	PART # SUFFIX ADD TO SMP CAT NO.	STOCK MODEL	LIST PRICE ADDER
PI Set-point Control Function	P		\$70
High Frequency Output (1000 Hz)	V		\$70

REGAL-BELOIT SpinMaster™ VMax AC Adjustable Speed Drives

Sensorless Vector Constant Torque, Micro Inverter



REGAL-BELOIT
SpinMaster™ VMax

Applications: Constant torque or constant horsepower applications. Typical applications include conveyors, packaging machinery, machine tool, printing equipment, and specialty equipment.

- Features:**
- Current limit to 200% with frequency foldback
 - Full output torque at 1Hz
 - Auto Tuning
 - Independent accel and decel adjustment
 - Adjustable DC injection braking
 - Programmable inputs/outputs
 - UL Listed and UL Certified for Canada under File No. E197830
 - IP20 enclosure
 - Unlimited lead length with microMAX™, Black Max® or Blue Max®, AC motor
 - 2 year warranty

Single or Three Phase Input / Three Phase Output

HP / kW	INPUT PHASE	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	STOCK MODEL	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
										IN / MM	IN / MM	IN / MM	
.5 / .37	1	208/240	5.4/4.7	2.5/2.2	T2112	★	\$532	D3	2	5.75/146	3.64/93	3.94/100	
	3		3.1/2.7										
1 / .75	1	208/240	10.6/9.2	4.8/4.2	T2114		\$599	D3	2.5	5.75/146	3.64/93	4.74/120	
	3		5.8/5.1										
1.5 / 1.1	1	208/240	13.9/12.0	6.9/6.0	T2115		\$711	D3	3.5	5.75/146	4.52/115	5.24/133	
	3		8.0/6.9										
2 / 1.5	1	208/240	14.8/12.9	7.8/6.8	T2116		\$786	D3	4.5	5.75/146	4.52/115	6.74/171	
	3		9.1/7.9										
3 / 2.2	1	208/240	19.7/17.1	11.0/9.6	T2117	★	\$956	D3	5	5.75/146	4.52/115	6.74/161	d, FN
	3		12.4/10.8										

Three Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	STOCK MODEL	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
									IN / MM	IN / MM	IN / MM	
1 / .75	208/240	5.8/5.1	4.8/4.2	T2214		\$551	D3	2.5	5.75/146	3.66/93	4.74/120	
1.5 / 1.1	208/240	8.0/6.9	6.9/6.0	T2215		\$649	D3	3	5.75/146	3.66/93	5.74/146	
2 / 1.5	208/240	9.1/7.9	7.8/6.8	T2216		\$715	D3	3.1	5.75/146	4.52/115	6.74/171	FN
3 / 2.2	208/240	12.4/10.8	11.0/9.6	T2217		\$853	D3	3.2	5.75/146	4.52/115	6.74/171	FN
5 / 3.7	208/240	19.6/17.1	17.5/15.2	T2218		\$1,097	D3	4.6	5.75/146	4.52/115	6.74/171	FN
7.5 / 5.5	208/240	28.0/25.0	25.0/22.0	T2219		\$1,498	D3	7.3	7.75/197	5.78/147	7.18/182	FN
10 / 7.5	208/240	34.0/32.0	30.0/28.0	T2220	★	\$1,790	D3	7.5	7.75/197	5.78/147	7.18/182	FN
.5 / .37	480	1.4	1.1	T2412		\$621	D3	1.9	5.75/146	3.66/93	4.74/120	
1 / .75	480	2.5	2.1	T2414		\$669	D3	2.4	5.75/146	3.66/93	4.74/120	
1.5 / 1.1	480	3.6	3.0	T2415		\$731	D3	2.9	5.75/146	3.66/93	5.74/146	
2 / 1.5	480	4.0	3.4	T2416	★	\$806	D3	3.1	5.75/146	3.66/93	5.74/146	FN
3 / 2.2	480	5.4	4.8	T2417		\$901	D3	3.2	5.75/146	3.66/93	5.74/146	FN
5 / 3.7	480	8.8	7.6	T2418		\$1,149	D3	4.6	5.75/146	4.52/115	6.74/171	FN
7.5 / 5.5	480	12.4	11.0	T2419	★	\$1,498	D3	7.2	7.75/197	5.78/147	7.18/182	FN
10 / 7.5	480	15.8	14.0	T2420		\$1,790	D3	7.5	7.75/197	5.78/147	7.18/182	FN
1 / .75	575	2.0	1.7	T2514		\$715	D3	2.4	5.75/146	4.52/115	5.24/133	
2 / 1.5	575	3.5	3.0	T2516		\$857	D3	3.1	5.75/146	4.52/115	6.74/171	
3 / 2.2	575	4.7	4.2	T2517		\$1,017	D3	4.1	5.75/146	4.52/115	6.74/171	FN
5 / 3.7	575	7.4	6.6	T2518	★	\$1,244	D3	4.7	5.75/146	4.52/115	6.74/171	FN
7.5 / 5.5	575	11.2	9.9	T2519		\$1,616	D3	7.1	7.75/197	5.76/147	7.18/182	FN
10 / 7.5	575	13.7	12.2	T2520		\$1,915	D3	7.4	7.75/197	5.76/147	7.18/182	FN

REGAL-BELOIT SpinMaster™, SpinMaster™ Plus and SpinMaster™ VMax AC Adjustable Speed Drives

Product Feature Directory

FEATURE DESCRIPTION	SpinMaster™	SpinMaster™ Plus	SpinMaster™ VMAX
GENERAL DESIGN FEATURES			
RATINGS & SPECIFICATIONS			
INPUT VOLTAGE / HP RANGE	0.33 - 1.5 Hp (0.25 - 1.1 kW)	N/A	N/A
(+10%,-15%)	0.33 - 15 Hp (0.25 - 11 kW)	0.25 - 20Hp (0.18 - 15kW)	0.5 - 10 Hp (0.37 - 7.5 kW)
	0.5 - 15 Hp (0.37 - 11 kW)	0.5 - 30 Hp (0.37 - 22 kW)	0.5 - 10 Hp (0.37 - 7.5 kW)
	N/A	1 - 25Hp (0.75 - 18.5kW)	0.5 - 10 Hp (0.37 - 7.5 kW)
OUTPUT FREQUENCY	0 - 240 Hz	0 - 240 Hz (1000 Hz option)	0 - 240 Hz
CARRIER FREQUENCY	4kHz to 10kHz (2kHz steps)	4kHz to 10kHz (2kHz steps)	2kHz, 4kHz, & 8kHz
OVERLOAD CAPACITY (60 SECONDS)	150%	150%	150%
TORQUE RATING	CONSTANT / 10:1	CONSTANT / 10:1	CONSTANT / 2000:1
DRIVE TYPE	V/Hz	V/Hz	VECTOR (sensorless)
AMBIENT TEMPERATURE	0 - 40°C	0 - 50°C	0 - 50°C
ENCLOSURE TYPES			
IP20 (CHASSIS)	STANDARD	STANDARD	STANDARD
COOLING	CONVECTION or HEAT SINK FAN	CONVECTION or HEAT SINK FAN	CONVECTION or HEAT SINK FAN
PERFORMANCE FEATURES			
PI SETPOINT CONTROL	N/A	OPTION	N/A
SLIP COMPENSATION	STANDARD	STANDARD	STANDARD
REVERSE ROTATION	STANDARD	STANDARD	STANDARD
DC INJECTION BRAKING UP TO 30% VOLTAGE	UP TO 3600 SECONDS	UP TO 3600 SECONDS	UP TO 999.9 SECONDS
2nd ADJUSTABLE ACCEL/DECCEL	STANDARD	STANDARD	STANDARD
2nd STOP COMMAND (e.g. FAST STOP)	STANDARD	STANDARD	STANDARD
RE-START INTO SPINNING MOTOR	STANDARD	STANDARD	STANDARD
BIPOLEAR SPEED REFERENCE	N/A	N/A	STANDARD
INPUT/OUTPUT INTERFACE AND OTHER FEATURES			
SPEED REFERENCE INPUTS			
KEYPAD	STANDARD	STANDARD	STANDARD
POTENTIOMETER	STANDARD	STANDARD	STANDARD
4 - 20mA	STANDARD	STANDARD	STANDARD
0 - 10 VDC	STANDARD	STANDARD	STANDARD
MOTOR OPERATED POT (MOP)	STANDARD	STANDARD	STANDARD
PRESET SPEEDS	7	7	7
ANALOG OUTPUTS			
0 - 10 VDC: SPEED or LOAD	N/A	STANDARD	STANDARD
2 - 10 VDC: SPEED or LOAD*	N/A	STANDARD	STANDARD
DIGITAL OUTPUTS			
PROGRAMMABLE STATUS INDICATIONS (e.g. RUN, FAULT, AT SPEED, etc.)	STANDARD	STANDARD	STANDARD
RELAY OUTPUTS	1 (Form A)	N/A	N/A
OPEN-COLLECTOR OUTPUTS	1	2	2
12 VDC POWER SUPPLY FOR AUX. RELAY	STANDARD	STANDARD	STANDARD
KEYPAD & DISPLAY FUNCTIONS			
DISPLAY TYPE	3 DIGIT LED	3 DIGIT LED	3 DIGIT LED
FREQUENCY (SPEED) DISPLAY	STANDARD	STANDARD	STANDARD
MOTOR LOAD DISPLAY	STANDARD	STANDARD	STANDARD
MOTOR VOLTAGE DISPLAY	STANDARD	STANDARD	STANDARD
DC BUS VOLTAGE DISPLAY	STANDARD	STANDARD	STANDARD
SERIAL COMMUNICATIONS			
RS - 232	N/A	N/A	N/A
RS - 485	N/A	STANDARD	STANDARD
MODBUS PROTOCOL	N/A	STANDARD	STANDARD
CONTROL I/O	11 ISOLATED TERMINALS	18 ISOLATED TERMINALS	18 ISOLATED TERMINALS
REMOTE KEYPAD (NEMA 4X)	OPTION	OPTION	OPTION
DYNAMIC BRAKING	OPTION	OPTION	OPTION
EPM PROGRAMMER COMPATIBLE	STANDARD	STANDARD	STANDARD

* 2 - 10 VDC signals can be converted to 4 - 20 mA by adding series resistance such that the total circuit resistance is 500 ohms.

Items in **BOLD BLUE** indicate key product differences.

REGAL-BELOIT SpinMaster™, SpinMaster™ Plus, and SpinMaster™ VMax AC Adjustable Speed Drives


Micro Inverter Accessories / Options



Electronic Programming Unit

Electronic Programming Unit allows off-line setup and replication of the drive's plug-in electronic programming module. RS-232 serial port allows downloading of configuration files from a PC

CAT. NO.	STOCK MODEL	DESCRIPTION	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.
T915	*	EPM programmer	\$729	D3	2



Dynamic Braking Module

Dynamic braking module through 10 HP, includes brake resistors and the control electronics in a convenient package. Modules can be panel or DIN rail mounted.

HP	CAT. NO.	STOCK MODEL	VOLTAGE	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.
.25 - .50	T931	*	208/240	\$233	D3	2
1 - 1.5	T933	*	208/240	\$272	D3	3
2 - 3	T935	*	208/240	\$370	D3	4
5	T936	*	208/240	\$482	D3	5
7.5	T937		208/240	\$609	D3	6
10	T938		208/240	\$735	D3	8
.25 - .50	T941	*	480	\$233	D3	2
1 - 1.5	T943	*	480	\$272	D3	3
2 - 3	T945	*	480	\$370	D3	4
5	T946	*	480	\$482	D3	5
7.5	T947		480	\$609	D3	6
10	T948		480	\$735	D3	8
1 - 1.5	T953	*	575	\$272	D3	3
2 - 3	T955	*	575	\$370	D3	4
5	T956	*	575	\$482	D3	5
7.5	T957		575	\$609	D3	6
10	T958		575	\$735	D3	8



DIN Rail Mounting Kits

Steel plates and fasteners for mounting AC drives or Dynamic Brake Modules on standard 35 mm DIN rails for panel building. Set of 6.

CAT. NO.	STOCK MODEL	DESCRIPTION	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.
T900	*	For 3.66" widths	\$132	D3	3
T901	*	For 3.66" or 4.52" widths	\$166	D3	3
T902	*	For 5.78" widths	\$198	D3	3



EPM Bulk Pack

Plug-in electronic programming modules (EPM) allows off-line setup and replication of program using electronic programming unit. Set of 10.

CAT. NO.	STOCK MODEL	DESCRIPTION	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.
T916	*	EPM bulk pack	\$142	D3	1



Remote Keypad

Remote keypad kit includes 8 foot connecting cable and gasket. Remote keypads are not interchangeable between drives.

CAT. NO.	STOCK MODEL	DESCRIPTION	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.
T920	*	For SpinMaster™	\$152	D3	2
T921	*	For SpinMaster™ Plus	\$187	D3	2
T922	*	For SpinMaster™ VMax	\$208	D3	2

Dynamic Braking Modules*

HP	CAT. NO.	STOCK MODEL	VOLTAGE	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.
15 - 20	T939		208/240	\$314	D3	10
15 - 30	T949		480	\$314	D3	10
15 - 25	T959		575	\$314	D3	10

*Dynamic braking resistors are sold and mounted separately.

Dynamic Braking Resistors**

HP	CAT. NO.	STOCK MODEL	VOLTAGE	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.
15 - 20	T969		208/240	\$345	D3	1
15 - 20	T969		480	\$345	D3	1
15 - 20	T970		575	\$345	D3	1
25 - 30	T971		480	\$583	D3	1
25 - 30	T972		575	\$583	D3	1

**Dynamic braking resistors are provided with mounting brackets.

Dynamic Braking Module Sizes

HP	HEIGHT	WIDTH	DEPTH
	IN/MM	IN/MM	IN/MM
.25 - 1.5	4.6/117	3.1/79	3.1/79
2 - 3	4.6/117	3.1/79	4.3/109
5	4.6/117	3.1/79	5.6/142
7.5 - 10	4.6/117	4.2/107	6.7/170
15 - 30	4.6/117	3.1/79	3.1/79

REGAL-BELOIT SpinMaster™ Micro AC Adjustable Speed Drives

Constant Torque, NEMA 1 Inverter



REGAL-BELOIT
SpinMaster®

Applications: Constant torque or constant horsepower applications. Typical applications include conveyors, packaging machinery, machine tool, printing equipment, and specialty equipment.

- Features:**
- NEMA 1 enclosure with epoxy finish
 - Current limit to 180% with frequency foldback
 - Adjustable carrier frequency
 - Independent accel and decel times
 - Adjustable DC injection braking
 - Serial Communication interface
 - Programmable inputs/outputs
 - UL Listed and UL Certified for Canada under File No. E197830
 - 2 year warranty

Single Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	STOCK MODEL	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
									IN / MM	IN / MM	IN / MM	
.25 / .19	120/240	6.0/3.0	1.4	T1110		\$757	D3	5	7.50/190	4.70/119	3.33/85	
.50 / .38	120/240	9.2/4.6	2.2	T1112	*	\$914	D3	7	7.50/190	6.12/3.63	3.63/92	
1 / .75	120/240	16.2/8.1	4.0	T1114	*	\$921	D3	7	7.50/190	6.12/3.63	4.22/107	
1.5 / 1.1	120/240	21/10.4	5.2	T1115	*	\$1,020	D3	7	7.50/190	6.12/3.63	4.22/107	
2 / 1.5	240	14.9	6.8	T1116	*	\$973	D3	9	7.50/190	6.12/3.63	5.12/130	
3 / 2.2	240	21.0	9.6	T1117	*	\$1,072	D3	9	7.50/190	6.12/3.63	5.12/130	

Three Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS 200/230 VAC	CAT. NO.	STOCK MODEL	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
									IN / MM	IN / MM	IN / MM	
.50 / .38	208/240	3.1/2.7	2.5/2.2	T1212	*	\$801	D3	6	7.50/190	4.70/119	3.63/92	
1 / .75	208/240	5.5/4.8	4.6/4.0	T1214	*	\$842	D3	6	7.50/190	4.70/119	4.33/110	
1.5 / 1.1	208/240	7.1/6.2	6.0/5.2	T1215	*	\$882	D3	6	7.50/190	4.70/119	4.33/110	
2 / 1.5	208/240	9.3/8.1	7.8/6.8	T1216	*	\$943	D3	9	7.50/190	6.12/3.63	5.12/130	
3 / 2.2	208/240	12.9/11.3	11.0/9.6	T1217	*	\$1,014	D3	9	7.50/190	6.12/3.63	5.12/130	
5 / 3.7	208/240	20.4/17.7	17.5/15.2	T1218	*	\$1,198	D3	11	7.88/200	6.12/3.63	5.94/151	
7.5 / 5.5	208/240	29.9/26.0	25.3/22.0	T1219	*	\$1,731	D3	13	9.38/238	7.86/200	6.84/174	FN
10 / 7.5	208/240	36.8/32.0	32.2/28.0	T1220	*	\$2,295	D3	15	11.25/286	7.86/200	6.84/174	FN
15 / 11	208/240	55.2/48.0	48.3/42.0	T1221	*	\$3,028	D3	19	12.75/324	7.86/200	6.84/174	FN
20 / 15	208/240	70.0/61.0	62.0/54.0	T1222	*	\$4,110	D3	21	12.75/324	10.26/261	7.74/197	FN
25 / 18.5	208/240	89.0/77.0	78.0/68.0	T1223	*	\$4,977	D3	38	15.75/400	10.26/261	8.35/212	FN
30 / 22	208/240	104/90.0	92.0/80.0	T1224	*	\$5,973	D3	44	15.75/400	10.26/261	8.35/212	FN
1 / .75	480	2.4	2.0	T1414	*	\$1,011	D3	6	7.50/190	4.70/119	3.63/92	
2 / 1.5	480	4.1	3.4	T1416	*	\$1,109	D3	7	7.50/190	6.12/3.63	4.22/107	
3 / 2.2	480	5.7	4.8	T1417	*	\$1,198	D3	9	7.50/190	6.12/3.63	5.12/130	
5 / 3.7	480	8.9	7.6	T1418	*	\$1,347	D3	9	7.50/190	6.12/3.63	5.12/130	
7.5 / 5.5	480	12.8	11.0	T1419	*	\$1,831	D3	11	9.38/238	7.86/200	6.25/159	
10 / 7.5	480	15.9	14.0	T1420	*	\$2,487	D3	13	9.38/238	7.86/200	6.84/174	FN
15 / 11	480	24.0	21.0	T1421	*	\$3,195	D3	15	11.25/286	7.86/200	6.84/174	FN
20 / 15	480	31.0	27.0	T1422	*	\$4,240	D3	17	12.75/324	7.86/200	6.84/174	FN
25 / 18.5	480	38.0	34.0	T1423	*	\$4,999	D3	21	12.75/324	10.26/261	7.74/197	FN
30 / 22	480	45.0	40.0	T1424	*	\$5,443	D3	21	12.75/324	10.26/261	7.74/197	FN
40 / 30	480	59.0	52.0	T1425	*	\$6,273	D3	35	15.75/400	10.26/261	8.35/212	FN
50 / 37.5	480	74.0	65.0	T1426	*	\$7,647	D3	44	19.75/502	10.26/261	8.55/217	FN
60 / 44	480	87.0	77.0	T1427	*	\$8,400	D3	44	19.75/502	10.26/261	8.55/217	FN
2 / 1.5	575	3.3	2.7	T1516	*	\$1,238	2.7	7	7.50/190	6.12/3.63	4.22/107	

AC DRIVES