

General Purpose, Single Phase

Totally Enclosed,



Features:

- Double sealed ball bearings, mechanically locked on shaft end
- Heavy gauge steel constructions
- Bolt-on, removable rigid base
- Suitable for horizontal or vertical mounting
- Capacitor start design for high starting torque
- Capacitor start/capacitor run design for higher efficiency, as noted
- 1.15 Service Factor (except as noted)
- Will accept brake kits, see Accessory section (except as noted)
- Will accept drip cover kits, see Accessories section
- UL Recognized and CSA Certified

C-Face Footed (Removable Base)

HP	RPM	VOLTS	FOUR-N ONE	FRAME LOAD	OVER NO.	CAT. NO.	MODEL	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/4	1200	115/208-230	◆	56C	NONE	G577	56C11F5302	★	\$333	F2	6.8/3.1-3.4	11.82	
1/3	1800	115/208-230	◆	56C	NONE	G570	56C17F5320	★	\$259	F2	6.6/3.1-3.3	11.82	68
	1200	115/208-230	◆	56C	NONE	G576	56C11F5303	★	\$371	F2	7.8/3.6-3.9	12.32	
1/2	3600	115/208-230	◆	56C	NONE	D311	56C34F5301	★	\$220	F2	8.4/4.0-4.2	11.82	
	1800	115/208-230	◆	56C	NONE	G571	56C17F5321	★	\$297	F2	8.8/4.2-4.4	11.82	68
	1200	115/208-230	◆	56C	NONE	G578	56B11F5303	★	\$453	F2	9.6/4.7-4.8	13.32	1.68
3/4	3600	115/208-230	◆	56C	NONE	D312	56C34F5302	★	\$266	F2	10.6/5.3-5.3	12.32	
	1800	115/208-230	◆	56C	NONE	G572	56C17F5322	★	\$357	F2	11.0/5.4-5.5	12.32	68
	1200	115/208-230	◆	56C	NONE	G579	56B11F5302	★	\$566	F2	11.4/5.8-5.7	13.82	1
1	3600	115/208-230	◆	56C	NONE	D313	56C34F5303	★	\$300	F2	11.2/5.7-5.6	12.32	
	1800	115/208-230	◆	56HC	NONE	G573	56C17F5323	★	\$380	F2	13.4/6.8-6.7	12.82	5,68
1 1/2	3600	115/208-230	◆	56C	NONE	D314	56B34F5326	★	\$378	F2	14.2/7.7-7.1	12.82	1
	1800	115/208-230	◆	56HC	NONE	G574	56B17F5305	★	\$436	F2	15.2/8.2-7.6	13.82	1,5,68
2	3600	115/208-230	◆	56HC	NONE	D315	56B34F5327	★	\$455	F2	16.6/9.1-8.3	13.82	1,5
	1800	115/208-230	◆	56HC	NONE	G575	56B17F5306	★	\$546	F2	20.0/10.8-10.0	14.82	1,5,17
3	3600	208-230	◆	56HC	NONE	D316	56B34F5328	★	\$608	F2	13.1-11.8	14.82	1,5

SINGLE PHASE