

**Single Phase,
ODP, Foot Mounted**

1/6 thru 10 Hp

NEMA 48 thru 215T

Applications: Compressors, pumps, conveyors, machine tools, air handling, and others.

Features: Copper windings, dynamically balanced rotors, ball bearings, heavy-gauge steel frames, and other industrial quality features.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)	
1/6	1800	48	L1200	246	K	9.13	18	49	115/230	1.9	C	30	
	1200	48	L1201	376	K	9.38	23	47	115/230	2.3	C	30	
1/4	1800	48	EL1203	321	K	9.76	23	74	115/230	1.3	C	1, 65	
		48	L1203	250	K	9.13	21	59.5	115/230	2.2	C	30	
		48	L1203M	287	K	9.13	20	55	115/230	2.5	C	30	
		48	L1204	402	K	9.75	25	48	115/230	3.2	C	30	
	1200	48	L1204	402	K	9.75	25	48	115/230	3.2	C	30	
		56	L1300	418	K	10.13	26	48	115/230	3.2	C	30	
1/3	3600	48	EL1205	293	K	9.76	26	72	115/208-230	1.6	C	65	
		48	L1205	236	K	9.13	20	55	115/208-230	3	C	30	
		48	L1206	287	K	9.13	21	60	115/230	3	C	30	
		48	L1206M	323	K	9.13	22	60	115/230	3	C	30	
	1800	56	EL1301	380	K	10.13	26	77	115/230	1.6	C	1, 65	
		56	L1301	290	K	9.51	22	60	115/230	3	C	30	
		56	L1301M	340	K	9.51	22	60	115/230	3	C	30	
		48	L1207	429	K	10.63	28	54	115/230	3.7	C	30	
	1200	56	L1302	429	K	11.01	29	54	115/230	3.7	C	30	
		48	L1208	261	K	9.13	22	57	115/230	3.7	C	30	
	1/2	3600	56	EL1303	323	K	10.13	23	68	115/230	2.5	C	65
			56	L1303	261	K	9.51	21	66	115/230	3.5	C	30
48			L1209	361	K	9.75	24	68	115/230	3.7	C	30	
1800		48	L1209M	401	K	9.38	24	62	115/230	4.2	C	30	
		56	EL1304	435	K	11.00	29	78.5	115/230	2.3	C	1, 65	
		56	L1304	321	K	10.13	24	68	115/230	3.7	C	30	
		56	L1304A	382	K	9.76	25	62	115/230	4.2	C	30	
		56	L1304M	401	K	9.76	25	62	115/230	4.2	C	30	
		1200	56/56H	L1305	645	K	11.75	38	62	115/230	4.1	C	30, 36, 65
3/4		3600	56	EL1306	394	K	11.00	29	72	115/230	3.9	C	65
			56	L1306	319	K	12.85	26	72	115/230	4.7	C	30
			56	L1306A	335	K	11.75	29	69	115/230	5.5	C	
	1800	56	EL1307	536	K	12.06	38	84	115/230	3.3	C	1, 65	
		56	L1307	396	K	11.51	32	68	115/230	5.1	C	30	
		56	L1307A	465	K	11.51	32	68	115/230	5.1	C	30	
		56	L1307M	477	K	11.51	32	68	115/230	5.1	C	30	
1200	56/56H	L1308	726	K	11.75	42	68	115/230	5	C	30, 36, 65		
1	3600	56	EL1309	414	K	11.00	32	74	115/208-230	5.1	C	65	
		56	L1309	334	K	11.01	31	65	115/230	7.5	C	30	
		56	L1309A	356	K	11.01	30	70	115/230	6.6	C		
	1800	56/56H	L1318	474	K	11.75	39	67	115/230	6.2	C	30, 36	
		56/56H	L1318M	516	K	11.75	39	67	115/230	6.2	C	2, 36	
		56	EL1310	584	K	12.94	42	84	115/230	4.3	C	1, 65	
		56	L1310	433	K	11.07	34	66	115/230	6.7	C	30	
		56H	L1310M	554	K	11.75	36	66	115/230	6.7	C	30, 36	
		143T	L1318T	494	L1	13.00	42	67	115/230	6.2	C	30	
		143T	L1318TM	516	L1	12.12	42	67	115/230	6.2	C	2	
		182	L1401	704	L1	12.75	50	70	115/230	7	C	30	
		182	L1401M	764	L1	12.75	48	70	115/230	7	C		
1200	184	L1407	1,235	L1	14.13	63	65	115/230	8	C	30		

(a) See notes on inside back flap.

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors

BALDOR • RELIANCE
Single Phase, ODP, Foot Mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status ^(a)	Notes ^(a)	
1 1/2	3600	56/56H	L1313A	490	K	11.75	40	68	115/230	9	C	30, 36	
		56H	EL1313	580	K	12.25	37	80	115/208-230	6.2	C	65	
		56H	L1313	469	K	11.75	34	77	115/230	6.4	C	30, 36, 65	
		143T	L1313T	469	L1	11.12	37	70	115/230	8.9	C	30	
	1800	56/56H	L1319	559	K	11.75	41	68	115/230	9	C	30, 36	
		56/56H	L1319M	623	K	11.75	42	68	115/230	9	C	36	
		56H	EL1319	765	K	14.00	51	85.5	115/230	6.3	C	1, 36, 65	
		143T	EL1319T	793	L1	13.00	49	85.5	115/230	6.3	C	1, 65	
		145T	L1319T	528	L1	12.12	42	68	115/230	9	C	30	
		145T	L1321T	634	L1	13.00	45	70	115/230	10.5	C	30	
		145T	L1321TM	687	L1	13.00	45	70	115/230	10.5	C		
		184	L1403	786	L1	12.75	56	68	115/230	9.5	C	30	
		184NA	L1403M	833	L1	12.75	56	68	115/230	9.5	C		
		2	3600	56/56H	L1317	623	K	11.75	43	70	115/230	13	C
56/56H	L1317A			641	K	11.75	44	70	115/230	12	C	30, 36	
56H	EL1317			771	K	11.75	46	75.5	115/230	9	C		
145T	L1320T			668	L1	12.12	46	71	115/230	11.5	C	30, 65	
1800	145T		L1322T	646	L1	13.00	48	75.5	115/208-230	10.2	C	65	
	145T		L1322TM	703	L1	13.00	45	78.5	115/230	9.2	C	65	
	182T		EL1405T	894	L1	15.87	65	82.5	115/230	8.8	C	1, 65	
	182T		L1405T	663	L1	15.00	65	71	115/230	12	C	30	
	184		L1405	825	L1	14.13	64	71	115/230	12	C	30	
	213NA		L1502	1,417	L1	14.32	82	69	115/230	12.5	C	30	
	1200		215	L1503	1,929	L1	15.94	104	68	115/230	14	C	30
	3		3600	182T	EL1406T	941	L1	15.00	74	81	115/230	12.3	C
182T		L1406T		760	L1	15.00	65	78	115/230	14	C	30	
1800		184T	EL1408T	936	L1	16.50	78	85.5	208-230	11.2	C	1, 65	
		184T	L1408T	717	L1	15.00	73	78	115/230	16	C	30, 65	
		184T	L1408TM	844	L1	15.00	78	78	115/230	16	C		
		215	L1505	1,570	L1	15.94	102	75	115/230	18	C	30	
		1200	215NA	L1506	2,254	L1	15.94	111	75	115/230	16	C	30, 65
5	3600	184T	EL1409T	1,118	L1	15.00	77	81.5	230	0	C	65	
		184T	L1409T	904	L1	15.00	76	75	230	23	C	30	
	1800	184T	EL1410T	1,069	L1	18.00	95	86.5	230	19.1	C	1, 65	
		184T	L1410T	850	LS	16.50	86	82.5	230	23	C	1, 30, 65	
		184T	L1410TM	1,027	L1	16.50	84	82.5	230	23	C	1, 30	
		184T	L1430T	778	L1	16.55	79	84	230	20.6	C	1, 30, 65	
		184T	L1430TM	1,027	L1	16.55	84	80	230	24	C	1, 30, 65	
		213T	L1508T	1,120	L1	16.32	113	77	230	27	C		
7 1/2	3600	213T	L1509T	1,397	L1	18.37	101	82.5	230	30	C	1, 30, 65	
	1800	215T	L1510T	1,216	L1	17.45	134	85.5	230	31	C	30, 65	
10	3600	215T	L1511T	1,762	L1	17.45	130	83	230	46	C	1, 30	
	1800	215T	L1512T	1,775	L1	17.45	140	85.5	230	39	C	2, 65	

^(a) See notes on inside back flap.

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors