

**F-2 Mount,
Three Phase,
TEFC and ODP,
Foot Mounted**

1 thru 60 Hp

NEMA 145T thru 364T

Applications: Pumps, compressors, fans, conveyors, machine tools and other applications requiring three phase F-2 mounted motors.

Features: Copper windings, ball bearings, heavy-gauge steel frame with base seam-welded. EFM Super-E® motors have NEMA Premium® efficiency and 3 year warranty.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
Totally Enclosed Fan Cooled												
2	1800	145T	EFM3558T	668	L1	14.19	49	86.5	208-230/460	2.7	A	1, 30
		145T	FM3558T	454	L1	13.31	42	84	208-230/460	3.1	D	
3	1800	182T	EFM3611T	741	L1	18.05	69	89.5	230/460	4.2	A	1, 30
		182T	FM3611T	536	L1	16.55	70	87.5	208-230/460	4.1	D	1
5	1800	184T	EFM3615T	811	L1	18.05	95	89.5	230/460	6.5	A	1, 30
		184T	FM3615T	617	L1	16.56	74	87.5	208-230/460	7.1	D	1
7 1/2	1800	213T	EFM3710T	1,173	L1	19.02	125	91.7	230/460	9.4	A	1, 30
		213T	FM3710T	788	L1	17.89	110	89.5	208-230/460	10.1	D	1
10	1800	215T	EFM3714T	1,318	L1	20.52	158	91.7	230/460	12.5	A	1, 30
		215T	FM3714T	957	L1	19.01	131	89.5	208-230/460	13.5	D	1
15	1800	254T	EFM2333T	2,033	L1	23.16	255	92.4	230/460	18.5	A	1, 30
		256T	EFM2334T	2,463	L1	23.16	286	93	230/460	24	A	1, 30
20	1800	284T	EFM4103T	3,220	L1	27.76	392	93.6	230/460	30	A	1, 30
30	1800	286T	EFM4104T	3,824	L1	27.76	444	93.6	230/460	36	A	1, 30
Open Drip Proof												
1	1800	145T	EFM3116T	547	L1	11.12	36	85.5	208-230/460	1.4	A	1
1 1/2	1800	145T	EFM3154T	572	L1	13.00	37	86.5	208-230/460	2.1	A	1
2	1800	145T	EFM3157T	613	L1	13.00	48	86.5	208-230/460	2.7	A	1
3	1800	182T	EFM3211T	661	L1	15.00	77	89.5	230/460	4	A	1
		182T	FM3211T	475	L1	14.00	54	86.5	208-230/460	4.2	D	1
5	1800	184T	EFM3218T	724	L1	16.50	84	89.5	230/460	6.6	A	1, 30
		184T	FM3218T	525	L1	15.00	68	87.5	208-230/460	6.9	D	
7 1/2	1800	213T	EFM3311T	1,064	L1	16.32	111	91	230/460	9.7	A	1, 30
		213T	FM3311T	744	L1	17.00	98	88.5	208-230/460	10	D	
10	1800	215T	EFM3313T	1,288	L1	17.45	123	91.7	230/460	12.5	A	1, 30
		215T	FM3313T	912	L1	16.32	114	89.5	208-230/460	13.4	D	
15	1800	254T	EFM2513T	1,824	L1	21.69	234	93	230/460	17.7	A	1, 30
		254T	FM2513T	1,378	L1	19.75	170	91	208-230/460	19	D	1
20	1800	256T	EFM2515T	2,290	L1	21.69	237	93	230/460	23.5	A	1, 30
		256T	FM2515T	1,774	L1	22.25	220	91.7	230/460	24	D	30
25	1800	284T	EFM2531T	2,791	L1	23.81	332	93.6	230/460	30	A	1, 30
		284T	FM2531T	2,150	L1	23.44	226	91.7	230/460	31	D	30
30	1800	286T	EFM2535T	3,052	L1	25.06	372	94.1	230/460	35	A	1, 30
		286T	FM2535T	2,514	L1	24.94	248	92.4	230/460	36	D	30
40	1800	324T	EFM2539T	3,982	L1	26.69	477	94.1	230/460	46	A	1, 30
		324T	FM2539T	3,205	L1	26.19	378	93	230/460	49	D	30
50	1800	326T	EFM2543T	4,394	L1	27.69	472	94.5	230/460	57	A	1, 30
		326T	FM2543T	3,762	L1	27.19	371	93	230/460	62	D	30
60	1800	364T	EFM2547T	5,532	L1	30.69	782	95	230/460	68	A	1, 30

(a) See notes on inside back flap.

■ Cast Iron Frame

Farm Duty Motors

Definite Purpose Motors

Unit Handling Motors

Brake Motors

200 & 575 Volt Motors

IEC Frame Motors

50 Hertz Motors

Inverter/Vector Motors & Controls

DC Motors and Controls

Soft Starters & Dynamic Brakes