


ME-CAN-DO Multi-Horsepower Fan & Blower - Direct Drive, PSC, Open Air Over

Resilient Ring, Thru-Bolt



Applications: Residential and commercial furnaces, air conditioners, exhaust fans, and other air handling equipment installed in clean and dry environments.

- Features:**
- Open end brackets
 - 2 1/4" Resilient rings
 - 1/2" x 5" long shaft with two flats 4.50" 90° apart
 - Automatic reset thermal protector
 - Weather resistant reversing plug
 - Reversible by reconnection
 - 36" long leads
 - Extended thru-bolts, 8-32 1/2" on shaft end and 3/4" on lead end
 - UL Recognized and CSA Certified
 - **Capacitor not included, see Accessories section**
 - Ball Bearings

| HP | RPM | VOLTS | FRAME | CAPACITOR (MFD) | SPEED RANGE | CAT. NO. | MODEL NO. | STOCK | LIST PRICE | MULT. SYMB. | F.L. AMPS | FRAME LENGTH |
|-----|--------|---------|-------|-----------------|--------------------|----------|-------------|-------|------------|-------------|-----------|--------------|
| 1/2 | | | | 10.0 | ALL | | | | | | 6.1 | |
| 1/3 | | | | 5.0 | ALL | | | | | | 5.2 | |
| 1/3 | | | | 7.5 | ALL | | | | | | 4.7 | |
| 1/4 | | | | 5.0 | MED-HI | | | | | | 3.6 | |
| 1/4 | 1075/4 | 115 | 48Y | 7.5 | MED-LO, LO | X077 | 48A11O11066 | ★ | \$135 | F1 | 3.2 | 5 |
| 1/5 | | | | 5.0 | MED-LO | | | | | | 2.8 | |
| 1/5 | | | | 7.5 | LO | | | | | | 2.5 | |
| 1/6 | | | | 5.0 | LO | | | | | | 2.4 | |
| 1/6 | | | | 7.5 | LO | | | | | | 2.0 | |
| 1/2 | | | | 10.0 | ALL | | | | | | 2.7 | |
| 1/3 | | | | 5.0 | ALL | | | | | | 2.3 | |
| 1/3 | | | | 7.5 | ALL | | | | | | 2.1 | |
| 1/4 | | | | 5.0 | MED-HI | | | | | | 1.6 | |
| 1/4 | 1075/4 | 208-230 | 48Y | 7.5 | MED-LO, LO | X073 | 48A11O11064 | ★ | \$139 | F1 | 1.4 | 4 3/4 |
| 1/5 | | | | 5.0 | MED-LO | | | | | | 1.3 | |
| 1/5 | | | | 7.5 | LO | | | | | | 1.1 | |
| 1/6 | | | | 5.0 | LO | | | | | | 1.1 | |
| 1/6 | | | | 7.5 | LO | | | | | | 0.9 | |
| 3/4 | | | | 20.0 | ALL | | | | | | 7.8 | |
| 1/2 | | | | 10.0 | ALL | | | | | | 7.1 | |
| 1/3 | 1075/4 | 115 | 48Y | 10.0 | MED-HI, MED-LO, LO | X074 | 48A11O11042 | ★ | \$161 | F1 | 4.9 | 6 |
| 1/4 | | | | 10.0 | MED-LO, LO | | | | | | 3.7 | |
| 1/5 | | | | 10.0 | LO | | | | | | 2.9 | |
| 3/4 | | | | 20.0 | HI | | | | | | 3.8 | |
| 1/2 | | | | 20.0 | MED-HI | | | | | | 2.7 | |
| 1/2 | | | | 10.0 | HI | | | | | | 3.7 | |
| 1/3 | 1075/4 | 208-230 | 48Y | 20.0 | MED-LO | X075 | 48A11O11063 | ★ | \$172 | F1 | 1.9 | 6 |
| 1/3 | | | | 10.0 | MED-HI | | | | | | 2.8 | |
| 1/4 | | | | 20.0 | LO | | | | | | 1.4 | |
| 1/4 | | | | 10.0 | MED-LO | | | | | | 2.6 | |
| 1/5 | | | | 10.0 | LO | | | | | | 1.6 | |