

**Grain Dryer/Vane
Axial Fan,
Single and
Three Phase,
TEAO and OPAO**

1.5 thru 15 Hp

NEMA 145TZ thru 215Z

Applications: Vane axial fan crop dryers.

Features: Shaft 3/4" longer than NEMA standard, shaft keyed, drilled and tapped with internal 1/4-20 tap 1" deep. Thermostats. Epoxy paint.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
Single Phase, Totally Enclosed Air Over												
1.5/3	3600	145TZ	UCLE153	950	L1	14.25	52	85.5	230	12.5	C	1, 30
3/4.5	3600	145TZ	UCLE3145	973	L1	15.62	60	82.5	230	12.5	C	2, 20
5/7.5	3600	182TZ	UCLE570	1,185	L1	16.88	94	84	230	20.5	C	2, 8
7.5/10	3600	182TZ	UCLE7510	1,281	L1	16.88	92	85.5	230	38	C	2, 20, 30
10/15	3600	215Z	UCLE1015	1,985	L1	18.56	160	89	230	46	C	2, 20
Single Phase, Open Air Over												
1.5/3	3600	145TZ	UCL153	864	L1	14.25	51	77	230	13.6	C	2, 20
3/4.5	3600	145TZ	UCL3145	919	L1	15.62	60	77.8	230	14.3	C	2, 20
		182Z	UCL345	957	L1	14.88	70	74	230	22	C	2, 20
5/7.5	3600	182TZ	UCL570	1,131	L1	16.88	93	80	230	35	C	2, 20
7.5/10	3600	182TZ	UCL710	1,213	L1	16.88	92	85	230	31	C	2, 20
7.5/10.5		215Z	UCL7510	1,536	L1	17.44	105	81	230	37	C	2, 20
10/15	3600	215Z	UCL1015	1,950	L1	17.81	134	84	230	44	C	2, 20
Three Phase, Totally Enclosed Air Over												
1.5/3	3600	145TZ	UCME153	668	L1	13.37	42	80	208-230/460	4.1	C	2, 20
3/4.5	3600	143TZ	UCME3145	706	L1	13.37	45	84.5	208-230/460	6	C	2, 8
		182Z	UCME345	754	L1	14.88	65	85.5	208-230/460	6	C	2, 20
5/7.5	3600	184TZ	UCME570	887	L1	15.38	66	84	230/460	9	C	2, 20, 30
7.5/10	3600	184TZ	UCME7510	1,040	L1	16.88	82	86.5	230/460	11.5	C	2, 20, 30
7.5/9.2		184TZ	UCME759	1,040	L1	16.88	85	89.5	208-230/460	8.5	C	2, 20
10/14	3600	215Z	UCME1014	1,328	L1	16.69	120	87.5	208-230/460	16.5	C	2, 20
Three Phase, Open Air Over												
1.5/3	3600	145TZ	UCM153	585	L1	13.37	39	80	208-230/460	4.1	C	2, 20
3/4.5	3600	143TZ	UCM3145	655	L1	13.37	45	81.5	208-230/460	6	C	2, 20
		182Z	UCM345	681	L1	14.25	54	84	208-230/460	5.8	C	2, 20
5/7.5	3600	184TZ	UCM575	836	L1	15.38	64	84	230/460	9.5	C	2, 20
7.5/10	3600	184TZ	UCM713	1,000	L1	16.88	86	84	208-230/460	12	C	2
10/15	3600	215Z	UCM1014	1,286	L1	16.69	101	85.5	208-230/460	18	C	2, 20

(a) See notes on inside back flap.

Farm Duty Motors

Definite Purpose Motors

Unit Handling Motors

Brake Motors

200 & 575 Volt Motors

IEC Frame Motors

50 Hertz Motors

Inverter/Vector Motors & Controls

DC Motors and Controls

Soft Starters & Dynamic Brakes