


# Condenser Fan/Heat Pump, PSC

## 56 Frame, Resilient Ring, Thru-Bolt



**Applications:** Direct drive condenser fans mounted vertically, shaft up or horizontal. These motors need to be mounted within the airflow of the fan for proper cooling.

- Features:**
- Enclosed shaft end bracket with vented frame
  - Ball bearings
  - 30" long leads (except P243)
  - Shaft slinger
  - 60°C ambient, as noted
  - Automatic reset thermal protector
  - Flat & keyway on shaft
  - UL Recognized and CSA Certified
  - **Capacitor not included, see Accessories section**

### Open Air Over, Shaft Up

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	FRAME LENGTH	SHAFT DIM.	FOOT NOTES
3/4	1075	208-230/460	56Y	P243	5KCP49RN9611S	★	\$351	F1	4.9-3.8/1.9	7 1/2	5/8 x 6	d,33
	1075	208-230/460	56Y	X207	56A11O5311	★	\$351	F1	3.9-3.6/1.8	8 1/4	5/8 x 6	37,45
1	1075	208-230/460	56Y	P244	5KCP49UN9613S	★	\$370	F1	6.3-5.0/2.5	8.4	5/8 x 6	d,34
	1075	208-230/460	56Y	X206	56A1105310	★	\$370	F1	5.4-5.2/2.6	10 1/16	5/8x6	37
1 1/2	1075	208-230/460	56Y	X271	56A11O5305	★	\$422	F1	7.7-7.6/3.8	9 3/4	5/8 x 6	34,45

### Dripproof

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	FRAME LENGTH	SHAFT DIM.	FOOT NOTES
1/2	825/1	115/208-230	56Y	P245	5KCP49PN9812S	★	\$477	F1	6.2/3.8-3.1	13.66	5/8 X 6	
	825/1	208-230	56Y	P246	5KCP49UN9811S	★	\$517	F1	5.8-5.6	14.47	5/8 X 6	
1	1075/3	115	56Y	P184	5KCP49UN9612S	★	\$495	F1	10.8	14.87	5/8 x 6	
	1075/3	200-230	56Y	P185	5KCP49UN9614S	★	\$495	F1	4.8-5.0	14.87	5/8 X 6	
	825/1	208-230/460	56Y	P180	5KCP49WN9813S	★	\$545	F1	6.3-6.4/3.2	11.24	5/8 x 6	

# Commercial Condenser Fan/Heat Pump, PSC

## Open Air Over, Belly Band, Shaft Up



**Applications:** Heavy duty design for commercial direct drive condenser fans mounted vertically, shaft up. These motors need to be mounted within the airflow of the fan for proper cooling.

- Features:**
- Open frame and end brackets
  - Shaft with flat, unless otherwise noted
  - Unique Rain Shield fits over shaft to protect motor in vertical shaft up position
  - Shaft slinger
  - Automatic reset thermal protector
  - 60°C ambient (as noted)
  - Ball bearings
  - UL Recognized and CSA Certified
  - **Capacitor not included, see Accessories section**

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	FRAME LENGTH	SHAFT DIM.	FOOT NOTES
0.4	1075	200-230/460	48Y	X445	48A11O1732		\$190	F1	3.0-2.8/1.4	5 1/2	1/2 x 4	
0.6	1075	200-230/460	48Y	P192	5KCP36PNB523S	★	\$209	F1	4.0/2.0	8 1/4	5/8 x 4 1/4	d
	1075	200-230/460	48Y	X446	48A11O1643	★	\$209	F1	3.0-3.6/1.8	6 7/8	1/2 x 4	
0.8	1075	200-230/460	48Y	P193	5KCP395NB4805	★	\$234	F1	4.0/2.0	14.19	1/2 x2 3/4	d
	1075	200-230/460	48Y	P194	5KCP39SNB481S	★	\$280	F1	4.0/2.0	9 1/3	5/8 x 4 7/8	d
	1075	200-230/460	48Y	X447	48A11O1642	★	\$280	F1	5.0-4.4/2.2	8 3/4	1/2 x 4	45
1	1075	200-230/460	48Y	P195	5KCP39SNB482S	★	\$302	F1	5.6/2.8	10 5/8	5/8 x 5 1/4 w/key/flat	d
	1075	200-230/460	56Y	X448	56A11O5314	★	\$302	F1	6.0-5.2/2.6	8 3/4	5/8 x 4 w/key/flat	45
	1075	575	56Y	P196	5KCP39TNB763T	★	\$302	F1	2.6	10 1/4	1/2 x 5 1/4	
1.5	1075	200-230/460	56Y	P197	5KCP39UNB767T	★	\$347	F1	8.1-7.8/3.9	10 1/4	5/8 spcl.	d
	1075	200-230/460	56Y	X449	56A11O5315	★	\$347	F1	7.0-7.0/3.5	9 1/4	5/8 x 4	45
	1075	575	56Y	P198	5KCP39UNB764T	★	\$347	F1	3.5	10 1/4	1/2 x 5 1/4	