


**Oil Field Pump,  
Three Phase,  
TEFC and ODP,  
Design D,  
Foot Mounted**

**3 thru 150 Hp**

**NEMA 213T thru 447T**

**Applications:** Beam pumping units, punch presses and applications requiring high torque and high slip.

**Features:** Two-part epoxy paint, moisture-resistant insulation, rodent screens, shaft slinger, F-2 position conduit box. TEFC motors have severe duty features. Includes thermostats.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
<b>Totally Enclosed Fan Cooled, 230/460/796 VAC</b>												
3	1200	213T	OF3764T	2,040	L1	19.32	225	79	230/460/796	3	C	1
5	1200	215T	OF3768T	2,261	L1	19.32	196	80	230/460/796	4.4	C	1
7 1/2	1200	254T	OF2276T	2,757	L1	23.25	249	84	230/460/796	7.4	C	1
10	1200	256T	OF2332T	3,070	L1	23.25	280	84	230/460/796	9	C	1
15	1200	284T	OF4100T	4,896	L1	27.56	390	87.5	230/460/796	11.6	C	1
20	1200	286T	OF4102T	5,916	L1	27.56	454	87.5	230/460/796	15	C	1
25	1200	324T	OF4111T	7,139	L1	30.27	561	87.5	230/460/796	19	C	1
<b>Totally Enclosed Fan Cooled, 460/796 VAC</b>												
30	1200	326T	OF4117T	8,656	L1	30.27	630	87.5	460/796	23	C	1
40	1200	365T	OF4308T	9,591	L1	32.84	845	88.5	460/796	30	C	1
50	1200	404T	OF4312T	12,423	L1	38.03	1090	87.5	460/796	34.6	C	1
60	1200	405T	OF4403T	15,366	L1	38.03	1171	88.5	460/796	42	C	1
75	1200	444T	OF4404T	16,665	L1	44.24	1648	88.5	460/796	51	C	1
100	1200	445T	OF4409T	21,662	L1	47.74	2100	90.2	460/796	67	C	1
125	1200	447T	OF4411T	27,807	L1	52.68	2516	91	460/796	86	C	1
150	1200	447T	OF44156T	32,846	L1	52.68	2889	91	460/796	102	C	1
<b>Open Drip Proof, 230/460/796 VAC</b>												
3	1200	213T	OF3303T	1,246	L1	18.13	117	78.5	230/460/796	3	C	2
5	1200	215T	OF3305T	1,654	L1	19.25	152	78.5	230/460/796	4.4	C	2
7 1/2	1200	254T	OF3307T	2,062	L1	24.18	209	81.5	230/460/796	7.2	C	2
		254T	OF3407T	2,261	L1	20.63	229	84	230/460/796	7.2	C	1
10	1200	256T	OF3310T	2,499	L1	24.18	234	82.5	230/460/796	9.2	C	2
		256T	OF3410T	2,642	L1	22.38	272	84	230/460/796	9	C	1
15	1200	284T	OF3315T	3,505	L1	26.31	288	85.5	230/460/796	13	C	1
		284T	OF3415T	3,703	L1	23.44	334	85.5	230/460/796	13.3	C	1
20	1200	286T	OF3320T	4,199	L1	26.31	318	84	230/460/796	17.2	C	1
		286T	OF3420T	4,393	L1	24.94	376	86.5	230/460/796	16.8	C	1
25	1200	324T	OF3325T	5,395	L1	29.18	436	85.5	230/460/796	20	C	1
		324T	OF3425T	5,740	L1	26.13	487	85.5	230/460/796	20	C	1
<b>Open Drip Proof, 460/796 VAC</b>												
30	1200	326T	OF3330T	6,564	L1	29.18	437	86.5	460/796	24	C	1
		326T	OF3430T	6,942	L1	27.63	517	86.5	460/796	25.4	C	1
40	1200	365T	OF3340T	8,362	L1	29.94	553	88.5	460/796	32	C	1
		365T	OF3440T	8,863	L1	29.69	749	87.5	460/796	31	C	1
50	1200	404T	OF3350T	9,777	L1	34.00	981	87.5	460/796	37	C	1
60	1200	404T	OF3360T	10,985	L1	34.00	1057	87.5	460/796	43	C	1
75	1200	404T	OF3375T	12,965	L1	34.00	1153	88.5	460/796	53	C	1
100	1200	445T	OF33100T	13,774	L1	39.62	1372	89.5	460/796	69.9	C	1
125	1200	449T	OF33125T	17,461	L1	48.06	2100	91	460/796	145	C	1

(a) See notes on inside back flap.

Custom TEFC motors available through 2,250 Hp; Open and WPll custom motors through 15,000 Hp. Contact your local Baldor•Reliance Sales Representative.

■ Cast Iron Frame

Farm Duty Motors

Definite Purpose Motors

Unit Handling Motors

Brake Motors

200 & 575 Volt Motors

IEC Frame Motors

50 Hertz Motors

Inverter/Vector Motors & Controls

DC Motors and Controls

Soft Starters & Dynamic Brakes