

Farm Duty / Agriculture, High Torque

Single Phase, TEFC



Features:

- Ball bearings, shaft end mechanically locked on C-face models
- 1.15 Service Factor (except as noted)
- Capacitor start design for high starting torque
- Capacitor start/capacitor run design for higher efficiency, as noted
- Low temperature manual reset thermal protector
- Totally enclosed and fully gasketed construction for dirty environments
- Condensate drains
- Shaft slinger
- UL Recognized and CSA Certified

Rigid Base

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/3	1800	115/230	56	F13E1	5KC42GN0051Y	★	\$266	F1	7.8/3.9	11.00	d
	1800	115/208-230	56	F101	56C17F5324	★	\$266	F1	6.6/3.1-3.3	11.82	
1/2	1800	115/208-230	56	F12E1	5KC46GN0050Y	★	\$304	F1	9.0/4.5-4.5	11.83	d
	1800	115/208-230	56	F102	56C17F5325	★	\$304	F1	8.8/4.2-4.4	11.82	
3/4	1800	115/230	56	F34E1	5KC46PN0062Y	★	\$363	F1	11.0/5.5	11.83	d,17
	1800	115/208-230	56	F103	56C17F5326	★	\$363	F1	11.0/5.4-5.5	12.32	
1	1800	115/208-230	143T	Z123	143TCFR5328	★	\$420	S1	13.4/6.8-6.7	12.87	
	1800	115/230	56	F10E1	5KC49TN0063Y	★	\$395	F1	13.2/6.6	12.96	d,17
	1800	115/208-230	143T	F104	56C17F5327	★	\$395	F1	13.4/6.8-6.7	12.82	
1 1/2	1800	115/208-230	145T	F15E1	5KCR48WN0292Y		\$495	S1	14.5/7.1-7.3	14.07	ES,1
	1800	115/208-230	145T	Z118	145TBFR5328	★	\$495	S1	15.2/8.2-7.6	13.87	1
	1800	115/208-230	56H	F100	5KCR48WN0273Y	★	\$486	F1	14.5/7.1-7.3	13.82	d,ES,1
	1800	115/208-230	56H	F105	56B17F5307	★	\$486	F1	15.2/8.2-7.6	13.82	ES,1
2	1800	115/230	145T	Z128	145TBFR5341	★	\$550	S1	18.8/9.4	14.87	1
	1800	208-230	145T	C1904	5KCR49ZN0564Y	★	\$550	S1	9.2	14.63	d,1,17
	1800	115/230	182T	Z119	182TCFR7072	★	\$599	S1	26.8/13.4	15.53	d
	1800	115/230	182T	Z1119	182TCFW7072	★	\$599	S1	24.0/12.0	14.46	13
3	1800	230	184T	Z120	184TCFR7061	★	\$746	S1	17.0	18.03	d
	1800	230	184T	Z1120	184TBFW17045	★	\$746	S1	14.2	14.96	1,13
5	1800	230	184T	Z121	184TBFR7737	★	\$908	S1	20.2	18.06	d,1
	1800	230	184T	Z1121	184TBFW7737	★	\$908	S1	19.5	17.45	1,13
7 1/2	1800	230	215T	Z122	215TBFW7029	★	\$1,347	S1	30.0	21.48	1

DEFINITE PURPOSE

C-Face Footed (Rigid Base)

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/3	1800	115/208-230	56C	F131	56C17F5358	★	\$325	F1	6.6/3.1-3.3	11.82	
1/2	1800	115/208-230	56C	F132	56C17F5912	★	\$363	F1	8.8/4.2-4.4	11.82	
3/4	1800	115/208-230	56C	F133	56C17F5913	★	\$422	F1	11/5.4-5.5	12.32	
1	1800	115/208-230	56C	F134	56C17F5914	★	\$454	F1	13.4/6.8-6.7	12.82	
1 1/2	1800	115/208-230	56HC	F135	56B17F5584	★	\$545	F1	15.2/8.2-7.6	13.82	1,5
2	1800	115/230	56HC	K319	56B17F5319	★	\$559	F1	18.8/9.4	14.82	1,5
3	1800	230	184TC	I314	184TBFR7041	★	\$838	S1	13.7	17.61	d,1
	1800	230	184TC	I1314	184TBFW7041	★	\$838	S1	12.8	14.96	1,13
5	1800	230	184TC	I315	184TBFR7034	★	\$1,000	S1	21.0	18.72	d,1
	1800	230	184TC	I1315	184TBFW7034	★	\$1,000	S1	19.5	17.45	1,13