

Centrifugal Pump (Jet Pump)

Three Phase, Totally Enclosed



Features:

- Service Factor, as noted
- Double sealed ball bearings, mechanically locked on shaft end
- Continuous Duty
- Nameplated 60/50 hertz, 190/380 volts at next lower HP, as noted
- 56C = carbon steel shaft with key, drip cover not included, see Accessories Section
- 56J = 416 stainless steel threaded shaft with slinger, drip cover included
- UL Recognized, CSA Certified, and CF Mark
- Drip cover not included, see Accessories section

C-Face Footless, 56C/56J

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	SERVICE FACTOR	F.L. AMPS	"C" DIM.	FOOT NOTES
1/3	3600	208-230/460	56C	K228	5K33FN41	★	\$192	F1	1.0	1.5-1.8/0.9	10.60	d
	3600	208-230/460	56C	P101	56T34T5306	★	\$192	F1	1.35	1.7-2.0/1.0	9.94	N,68
1/2	3600	200-230/460	56C	K229	5K35JN46	★	\$213	F1	1.6	2.1-2.0/1.0	10.93	d
	3600	208-230/460	56C	P102	56T34F5321	★	\$213	F1	1.15	2.1-2.2/1.1	11.82	68
	3600	200-230/460	56J	K230	5K35JN47	★	\$308	F1	1.6	2.1-2.0/1.0	11.40	48
	1800	208-230/460	56J	K550	5K42HN4133	★	\$374	F1	1.0	2.3-2.2/1.1	11.52	48
3/4	3600	200-230/460	56C	K231	5K36MN340	★	\$253	F1	1.5	2.6-2.6/1.3	11.36	d
	3600	208-230/460	56C	P103	56T34F5322	★	\$253	F1	1.15	3.0-3.2/1.6	11.82	68
	3600	208-230/460	56J	KG232	5K36MN339	★	\$340	F1	1.5	2.6-2.6/1.3	11.90	48
1	3600	200-230/460	56C	K233	5K38RN44	★	\$283	F1	1.4	3.2-3.0/1.5	12.36	d
	3600	208-230/460	56C	P104	56T34F5323	★	\$283	F1	1.15	3.7-3.7/1.85	11.82	68
	3600	200-230/460	56J	KG234	5K38RN49	★	\$391	F1	1.4	3.2-3.0/1.5	12.90	48
1 1/2	3600/3000	208-220/460	56C	K642	5K49JN2534	★	\$329	F1	1.15	4.8-4.6/2.3	11.82	d,68
	3600	208-230/460	56C	P105	56T34F5324	★	\$329	F1	1.15	4.6/2.3	11.82	68
	3600	200-230/460	56J	KG236	5K49PN2330	★	\$420	F1	1.3	4.8-4.2/2.1	12.95	48
2	3600/3000	208-230/460	56C	K637	5K46MN2533	★	\$382	F1	1.15	6.0-6.0/3.0	12.32	d,68
	3600	208-230/460	56C	P106	56T34F5325	★	\$382	F1	1.15	6.0-6.0/3.0	12.32	68
	3600	200-230/460	56J	K238	5K49SN2184	★	\$477	F1	1.2	5.8-5.4/2.7	13.48	48
3	3600	208-230/460	56C	K239	5K49ZN2189	★	\$414	F1	1.0	8.0/4.0	14.25	d
	3600	208-230/460	56C	P107	56T34F5326	★	\$414	F1	1.15	8.4-7.6/3.8	13.32	68
	3600	208-230/460	56J	K240	5K49ZN2190	★	\$578	F1	1.0	8.0/4.0	14.79	48



Features:

- Service Factor, as noted
- Double sealed ball bearings, mechanically locked on shaft end
- Continuous Duty
- Nameplated 60/50 hertz, 190/380 volts at next lower HP, as noted
- 56C = carbon steel shaft with key, drip cover not included, see Accessories Section
- 56J = 416 stainless steel threaded shaft with slinger, drip cover included
- UL Recognized, CSA Certified, and CF Mark
- Drip cover not included, see Accessories section

C-Face Footed (Removable Base), 56J

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	SERVICE FACTOR	F.L. AMPS	"C" DIM.	FOOT NOTES
1/3	3600	208-230/460	56J	J060	56T34T5308		\$209	F1	1.15	1.7-2.0/1.0	10.44	N,68
1/2	3600	200-220/440	56J	K1333	5K35JN4176	★	\$230	F1	1.0	2.1-2.0/1.0	11.44	d,82
	3600	208-230/460	56J	J061	56T34F5342	★	\$230	F1	1.15	2.1-2.2/1.1	12.32	68
3/4	3600/3000	208-230/440	56J	K630	5K36MN4157	★	\$270	F1	1.0	2.8-2.9/1.5	11.90	d,82
	3600	208-230/460	56J	J062	56T34F5343	★	\$270	F1	1.15	3.0-3.2/1.6	12.32	68
1	3600	200-230/460	56J	K245	5K38RN117	★	\$300	F1	1.4	3.2-3.0/1.5	12.90	d,48,82,
	3600	208-230/460	56J	J063	56T34F5344	★	\$300	F1	1.15	3.7-3.7/1.85	12.32	68
1 1/2	3600	200-230/460	56J	K246	5K49PN2350	★	\$361	F1	1.3	4.8-4.2/2.1	12.95	d,48,82
	3600	208-230/460	56J	J064	56T34F5345	★	\$361	F1	1.15	4.7-4.6/2.3	12.32	68
2	3600	208-230/460	56J	J065	56T34F5346	★	\$414	F1	1.15	6.0-6.0/3.0	12.82	68
3	3600	208-230/460	56J	J066	56T34F5347	★	\$472	F1	1.15	8.4-7.6/3.8	13.82	68