

# Centrifugal Pump (Jet Pump)

## Three Phase, Dripproof



### Features:

- Service Factor, as noted
- Double sealed ball bearings, mechanically locked on shaft end
- Continuous Duty
- Nameplated 60/50 hertz, 190/380 volts at next lower HP, as noted
- 56C = carbon steel shaft with key, drip cover not included, see Accessories Section
- 56J = 416 stainless steel threaded shaft with slinger, drip cover included
- UL Recognized and CSA Certified
- Drip cover not included, see Accessories section

### C-Face Footless, 56C/56J

HP	RPM	VOLTS	FRAME	CAT NO.	MODEL NO.	STOCK	FORMER CAT NO.	FORMER MODEL NO.	LIST PRICE	MULT. SYMB.	SERVICE FACTOR	F.L. AMPS	"C" DIM.	FOOT NOTES
1/3	3600	208-230/460	56C	KG215	5K35FN55	★	P001	56T34D5310	\$166	F1	1.75	1.5-1.8/0.9	9.90	68
	3600	208-230/460	56J	K748	5K35FN101	★	J040	56T34D5347	\$166	F1	1.75	1.5-1.8/0.9	10.40	48
1/2	3600	208-230/460	56C	K216	5K36JN57	★	P002	56T34D5311	\$188	F1	1.6	2.0-2.0/1.0	10.31	48,68
	3600	208-230/460	56J	K217	5K36JN56	★	J041	56T34D5348	\$188	F1	1.6	2.0-2.0/1.0	10.82	48,68
	1800	208-230/460	56J	K553	5K42HN4139	★			\$369	F1	1.25	2.3-2.2/1.1	10.41	48
3/4	3600	208-230/460	56C	K218	5K37MN37	★	P003	56T34D5312	\$226	F1	1.5	2.6-2.6/1.3	10.70	48,68
	3600	208-230/460	56J	KG219	5K37MN38	★	J042	56T34D5349	\$226	F1	1.5	2.6-2.6/1.3	11.22	48,68
	1800	208-230/460	56J	K555	5K46KN4141	★			\$434	F1	1.25	3.3-3.0/1.5	11.24	48
1	3600	208-230/460	56C	K220	5K38PN47	★	P004	56T34D5313	\$257	F1	1.4	3.3-3.2/1.6	11.30	48,68
	3600	208-230/460	56J	K221	5K38PN48	★	J043	56T34D5350	\$257	F1	1.4	3.3-3.2/1.6	11.82	48,68
	1800	208-230/460	56J	K750	5K46MN4144	★			\$449	F1	1.15	3.6-3.8/1.9	11.24	48
1 1/2	3600	208-230/460	56C	K222	5K46KN2173	★	P005	56T34D5314	\$313	F1	1.3	5.0-4.8/2.4	10.73	48,68
	3600	208-230/460	56J	K223	5K46KN2172	★	J044	56T34D5351	\$313	F1	1.3	5.0-4.8/2.4	11.24	48,68
	1800	208-230/460	56J	K751	5K49PN4121	★			\$496	F1	1.15	5.8-5.6/2.8	11.84	48
2	3600	208-230/460	56C	K224	5K49NN2180	★	P006	56T34D5315	\$367	F1	1.2	6.0-6.0/3.0	11.33	48,68
	3600	208-230/460	56J	K225	5K49NN2178	★	J045	56T34D5352	\$367	F1	1.2	6.0-6.0/3.0	11.84	48,68
3	3600	208-230/460	56C	K226	5K48TN2182	★	P007	56T34D5316	\$412	F1	1.15	8.9-8.2/4.1	12.61	48,68
	3600	208-230/460	56J	K227	5K48TN2181	★	J046	56T34D5353	\$412	F1	1.15	8.9-8.2/4.1	13.12	48,68



### Features:

- Service Factor, as noted
- Double sealed ball bearings, mechanically locked on shaft end
- Continuous Duty
- Nameplated 60/50 hertz, 190/380 volts at next lower HP, as noted
- 56C = carbon steel shaft with key, drip cover not included, see Accessories Section
- 56J = 416 stainless steel threaded shaft with slinger, drip cover included
- UL Recognized and CSA Certified
- Drip cover not included, see Accessories section

### C-Face Footed (Rigid Base), 56J

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	SERVICE FACTOR	F.L. AMPS	"C" DIM.	FOOT NOTES
1/3	3600	208-230/460	56J	J047	56T34D5368		\$170	F1	1.75	1.2-1.1/55	10.43	68
1/2	3600	208-230/460	56J	J048	56T34D5367	★	\$192	F1	1.6	2.1-2.2/1.1	10.93	68
3/4	3600	208-230/460	56J	K1483	5K37MN3543	★	\$230	F1	1.5	2.6-2.6/1.3	11.22	d,48
	3600	208-230/460	56J	J049	56T34D5365	★	\$230	F1	1.5	2.6-2.6/1.3	11.22	68
1	3600	208-230/460	56J	J050	56T34D5366	★	\$261	F1	1.4	3.7-3.7/1.85	10.93	68
1 1/2	3600	208-230/460	56J	K1484	5K46KN2082	★	\$317	F1	1.15	5.0-4.8/2.4	11.24	d,48
	3600	208-230/460	56J	J051	56T34D5369	★	\$317	F1	1.15	5.0-4.8/2.4	11.24	68
2	3600	208-230/460	56J	J052	56T34D5370	★	\$371	F1	1.2	6.4-6.2/3.1	10.93	68
3	3600	208-230/460	56J	J053	56T34D5371	★	\$416	F1	1.15	8.9-8.4/4.2	11.93	68