

**Close-Coupled Pump, 3 thru 10 Hp
Single Phase,
TEFC and ODP**

NEMA 182 thru 215 (JM, JP, TCZ)

Applications: Pumping systems where only single phase power is available.



Features: Heavy-gauge steel frame construction, corrosion resistant finish, ball bearings, suitable for mounting in any position.

| Hp | RPM | NEMA Frame | Catalog Number | List Price | Mult. Sym. | "C" Dim. | Aprx. Wt. (lb) | Full Load Efficiency | Voltage | Full Load Amps | EISA Status (a) | Notes (a) |
|--|------|------------|----------------|------------|------------|----------|----------------|----------------------|-------------|----------------|-----------------|-----------|
| Totally Enclosed Fan Cooled, Mechanical Seal, Type JM | | | | | | | | | | | | |
| 3 | 3600 | 182JM | JML3606T | 912 | L1 | 18.06 | 78 | 76 | 115/230 | 14.5 | C | 1, 30 |
| 5 | 3600 | 184JM | JML3608T | 1,216 | L1 | 19.55 | 91 | 83 | 230 | 19.5 | C | 2, 20 |
| Open Drip Proof, Mechanical Seal, Type JM | | | | | | | | | | | | |
| 3 | 3600 | 182JM | JML1406T | 870 | L1 | 16.50 | 70 | 78 | 115/208-230 | 14 | C | |
| | 1800 | 184JM | JML1408T | 998 | L1 | 16.50 | 77 | 78 | 115/230 | 16 | C | 30 |
| 5 | 3600 | 184JM | JML1409T | 1,229 | L1 | 16.50 | 78 | 80 | 230 | 21.5 | C | 1, 30 |
| | 1800 | 213JM | JML1508T | 1,416 | L1 | 18.19 | 118 | 77 | 230 | 27 | C | |
| 7 1/2 | 3600 | 213JM | JML1509T | 1,763 | L1 | 18.19 | 116 | 81 | 230 | 37 | C | 30 |
| | 1800 | 215JM | JML1510T | 1,865 | L1 | 19.31 | 137 | 85.5 | 230 | 31 | C | 30 |
| 10 | 3600 | 215JM | JML1511T | 2,168 | L1 | 19.31 | 139 | 83 | 230 | 46 | C | 1, 30 |
| | 1800 | 215JM | JML1512T | 2,308 | L1 | 20.95 | 155 | 84 | 230 | 41 | C | 1, 30 |
| Open Drip Proof, Packed Pump, Type JP | | | | | | | | | | | | |
| 3 | 3600 | 182JP | JPL1406T | 870 | L1 | 19.57 | 71 | 78 | 115/230 | 14 | C | 30 |
| | 1800 | 182JP | JPL1408T | 998 | L1 | 19.57 | 81 | 78 | 115/230 | 16 | C | 30 |
| 5 | 3600 | 184JP | JPL1409T | 1,229 | L1 | 19.57 | 88 | 80 | 230 | 21.5 | C | 1, 30 |
| | 1800 | 213JP | JPL1508T | 1,416 | L1 | 22.07 | 124 | 77 | 230 | 27 | C | |
| 7 1/2 | 3600 | 213JP | JPL1509T | 1,763 | L1 | 22.07 | 118 | 81 | 230 | 37 | C | 30 |
| | 1800 | 215JP | JPL1510T | 1,865 | L1 | 23.19 | 142 | 85.5 | 230 | 31 | C | 30 |
| 10 | 3600 | 215JP | JPL1511T | 2,168 | L1 | 23.19 | 145 | 83 | 230 | 46 | C | 1, 30 |
| | 1800 | 215JP | JPL1512T | 2,308 | L1 | 20.95 | 157 | 84 | 230 | 41 | C | 1, 30 |
| Open Drip Proof, West Coast Fit, Type TCZ | | | | | | | | | | | | |
| 3 | 3600 | 182TCZ | WCL1406T | 876 | L1 | 12.38 | 78 | 78 | 115/230 | 14 | C | 30 |
| | 1800 | 184TCZ | WCL1408T | 1,005 | L1 | 12.38 | 88 | 78 | 115/230 | 16 | C | 30 |
| 5 | 3600 | 184TCZ | WCL1409T | 1,240 | L1 | 12.38 | 92 | 75 | 230 | 23 | C | 1, 30 |
| | 1800 | 213TCZ | WCL1508T | 1,428 | L1 | 21.25 | 122 | 77 | 230 | 27 | C | |
| 7 1/2 | 3600 | 213TCZ | WCL1509T | 1,775 | L1 | 21.25 | 117 | 81 | 230 | 37 | C | 30 |
| 10 | 3600 | 215TCZ | WCL1511T | 2,188 | L1 | 22.38 | 139 | 83 | 230 | 46 | C | 1, 30 |

(a) See notes on inside back flap.

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors