

# Centrifugal Pump (Jet Pump)

## Single Phase, Dripproof



### Features:

- Service Factor, as noted
- Double sealed ball bearings, mechanically locked on shaft end
- Capacitor start design for high starting torque
- Capacitor start/capacitor run design for higher efficiency, as noted
- Fixed CW rotation, viewed opposite shaft end
- Automatic reset thermal protector
- 56C = carbon steel shaft with key, drip cover not included, see Accessories Section
- 56J = 416 stainless steel threaded shaft with slinger, drip cover included
- UL Recognized and CSA Certified

### C-Face Footless, 56C/56J

| HP    | RPM       | VOLTS       | FRAME | CAT. NO. | MODEL NO.     | STOCK | FORMER CAT. NO. | FORMER MODEL NO. | LIST PRICE | MULT. SYMB. | SERVICE FACTOR | F.L. AMPS      | "C" DIM. | FOOT NOTES |
|-------|-----------|-------------|-------|----------|---------------|-------|-----------------|------------------|------------|-------------|----------------|----------------|----------|------------|
| 1/3   | 3600      | 115/230     | 56C   | J1025    | 5KC37FN71X    | *     | J025            | 56C34D2111       | \$143      | F1          | 1.75           | 6.4/3.2        | 10.71    |            |
|       | 3600      | 115/230     | 56J   | C329     | 5KC37FN65X    | *     | J033            | 56C34D2110       | \$151      | F1          | 1.75           | 6.4/3.2        | 11.22    | 15         |
|       | 1800/1500 | 115/208-230 | 56J   | C683     | 5KC36LN84X    | *     |                 |                  | \$326      | F1          | 1.35           | 6.0/3.2-3.0    | 10.82    | 15,50      |
| 1/2   | 3600      | 115/230     | 56C   | C330     | 5KC36JN268X   | *     | J009            | 56C34D2097       | \$157      | F1          | 1.6            | 7.6/3.8        | 10.31    |            |
|       | 3600      | 115/230     | 56J   | C331     | 5KC36JN269X   | *     | J034            | 56C34D2096       | \$164      | F1          | 1.6            | 7.6/3.8        | 10.82    | 15         |
| 3/4   | 3600      | 115/230     | 56C   | C332     | 5KC39NN50X    | *     | J013            | 56C34D2103       | \$185      | F1          | 1.5            | 11.2/5.6       | 11.84    |            |
|       | 3600      | 115/230     | 56J   | C333     | 5KC39QN3219X  | *     | J035            | 56C34D2102       | \$192      | F1          | 1.5            | 11.2/5.6       | 12.40    | 15         |
|       | 2900      | 110/220     | 56C   | CG732    | 5KC39RN114T   | *     |                 |                  | \$318      | F1          | 1.5            | 9.8/4.9        | 12.60    | 50         |
| 1     | 3600      | 115/230     | 56C   | C334     | 5KC39RN44X    | *     | J017            | 56C34D1173       | \$207      | F1          | 1.4            | 13.2/6.6       | 12.59    |            |
|       | 3600      | 115/230     | 56J   | C335     | 5KC39RN45X    | *     | J036            | 56C34D1172       | \$213      | F1          | 1.4            | 13.2/6.6       | 13.14    | 15         |
| 1 1/2 | 3600      | 115/208-230 | 56C   | C336     | 5KC49NN2140X  | *     | J019            | 56B34D2025       | \$283      | F1          | 1.3            | 18.4/9.8-9.2   | 11.38    |            |
|       | 3600      | 115/230     | 56J   | C337     | 5KC49NN2167X  | *     | J037            | 56B34D2024       | \$300      | F1          | 1.3            | 18.4/9.2       | 11.89    |            |
| 2     | 3600      | 115/208-230 | 56C   | C338     | 5KC49TN2141X  | *     | J021            | 56B34D5325       | \$351      | F1          | 1.2            | 21.2/11.5-10.6 | 13.22    |            |
|       | 3600      | 115/208-230 | 56J   | C339     | 5KC49TN2170X  | *     | J038            | 56B34D5326       | \$368      | F1          | 1.2            | 21.2/10.6      | 13.73    |            |
| 3     | 3600      | 115/230     | 56C   | C340     | 5KCR48TN2142T | *     | J023            | 56B34D5327       | \$557      | F1          | 1.15           | 29.4/14.7      | 12.66    | 1          |
|       | 3600      | 115/230     | 56J   | C341     | 5KCR48TN2174T | *     | J039            | 56B34D5328       | \$587      | F1          | 1.15           | 29.4/14.7      | 13.17    | 1,15       |

### C-Face Footed (Rigid Base), 56J

| HP    | RPM  | VOLTS       | FRAME | CAT. NO. | MODEL NO.  | STOCK | LIST PRICE | MULT. SYMB. | SERVICE FACTOR | F.L. AMPS    | "C" DIM. | FOOT NOTES |
|-------|------|-------------|-------|----------|------------|-------|------------|-------------|----------------|--------------|----------|------------|
| 1/3   | 3600 | 115/208-230 | 56J   | J054     | 56C34D2118 | *     | \$155      | F1          | 1.75           | 5.6/2.7-2.8  | 10.94    |            |
| 1/2   | 3600 | 115/208-230 | 56J   | J055     | 56C34D2119 | *     | \$168      | F1          | 1.6            | 7.4/3.5-3.7  | 11.19    |            |
| 3/4   | 3600 | 115/208-230 | 56J   | J056     | 56C34D2120 | *     | \$196      | F1          | 1.5            | 9.8/4.8-4.9  | 11.44    |            |
| 1     | 3600 | 115/208-230 | 56J   | J057     | 56C34D2121 | *     | \$218      | F1          | 1.4            | 12.0/6.2-6.0 | 12.44    |            |
| 1 1/2 | 3600 | 115/208-230 | 56J   | J058     | 56B34D2033 | *     | \$304      | F1          | 1.3            | 13.4/7.4-6.7 | 12.43    | 1          |
| 2     | 3600 | 115/208-230 | 56J   | J059     | 56B34D5341 | *     | \$374      | F1          | 1.2            | 18.2/9.8-9.1 | 11.94    | 1          |

## Single Phase, Totally Enclosed



### Features:

- Service Factor, as noted
- Double sealed ball bearings, mechanically locked on shaft end
- Capacitor start design for high starting torque
- Capacitor start/capacitor run design for higher efficiency, as noted
- Reversible CW rotation, viewed opposite shaft end
- Automatic reset thermal protector
- 56C = carbon steel shaft with key, drip cover not included, see Accessories Section
- 56J = 416 stainless steel threaded shaft with slinger, drip cover included
- UL Recognized and CSA Certified

### C-Face Footless, 56C/56J

| HP  | RPM  | VOLTS   | FRAME | CAT. NO. | MODEL NO.     | STOCK | LIST PRICE | MULT. SYMB. | SERVICE FACTOR | F.L. AMPS | "C" DIM. | FOOT NOTES |
|-----|------|---------|-------|----------|---------------|-------|------------|-------------|----------------|-----------|----------|------------|
| 1/3 | 3600 | 115/230 | 56J   | C1336    | 5KC33FN4180X  | *     | \$262      | F1          | 1.0            | 5.6/2.8   | 11.87    |            |
| 1/2 | 3600 | 115/230 | 56J   | C465     | 5KC39QN3218X  | *     | \$326      | F1          | 1.15           | 7.4/3.7   | 11.9     | 15         |
| 3/4 | 3600 | 115/230 | 56C   | C847     | 5KC37NN115X   | *     | \$347      | F1          | 1.0            | 9.8/4.9   | 11.76    |            |
| 1   | 3600 | 115/230 | 56J   | C352     | 5KC49NN2135X  | *     | \$374      | F1          | 1.15           | 13.0/6.5  | 12.95    | 15         |
| 2   | 3600 | 115/230 | 56J   | C878     | 5KCR49TN2164T | *     | \$562      | F1          | 1.0            | 17.8/8.9  | 14.79    | ES,1,15    |

Catalog numbers in ( ) are GE catalog numbers that are no longer valid and have been replaced by MEMC/GE catalog numbers.